
DELTALIGHT




M26L - BOXY L SOFT 93045 MDL

REFERENCE 10735 9030 B-FBR

AVAILABLE IN
NOIR-NOIR 10735 9030 B-B
NOIR-FLEMISH BRONZE 10735 9030 B-FBR
NOIR-FLEMISH GOLD 10735 9030 B-FG
BLANC-BLANC 10735 9030 W-W





View on website

General info	
LOCATION	interieur
INSTALLATION	Systèmes basse tension Monté sur systèmes basse tension
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.4
ADJUSTABILITY	non réglable
INFORMATION	REFLECTOR WFL-45° EXCL.LED POWER SUPPLY 48V-DC

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = dimmable 1 à 10 V ou DALI ou boutton poussoir
ENERGY CLASS	F
CERTIFICATION	CB, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 10,2W / CRI>90 (R9: 50) / 3000K-1800K / 1038lm
SDMC	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	45°
LED TECHNICS (LIGHT SOURCE)	1038lm // 10,2W // 109lm/W
LED TECHNICS (LUMINAIRE)	805lm // 12W // 69lm/W

Remarks

Take a look at our MAGNETIC PROFILES movie

Requirements

LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR

Accessories

BOXY HONEYCOMB
BOXY SOFTENING LENS
BOXY GLASS SBL

DELTALIGHT

M26L - BOXY L SOFT 93045 MDL

10735 9030 B-FBR

For detailed installation instructions, please consult the manual : **10735_XXX0_HAND.pdf**


FINISH YOUR SPECIFICATION

le cable d'alimentation

of Fixtures

web2print_power_supply_info_box

Min current | Max current



21032 0030 SMART 48 MODULATOR PLUG-IN WD 27


Dimtype: WDL = dimmable sans fil

SMART 48

of Fixtures


web2print_power_supply_info_box

Min current | Max current



300 90 011 SMART 48 MODULATOR DIM9 27

Dimtype: 1 à 10 V ou DALI ou boutton poussoir



300 90 012 SMART 48 MODULATOR WD 27


Dimtype: WDL = dimmable sans fil

les alimentations led

of Fixtures


web2print_power_supply_info_box

Min current | Max current



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN 14

Dimtype: non dimmable




300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN 34

Dimtype: non dimmable

M26L - BOXY L SOFT 93045 MDL


10735 9030 B-FBR



21012 0230 LED POWER SUPPLY 48V-DC / 100W 14

Dimtype: non dimmable

Cutout dimension (mm): 40




21012 0240 LED POWER SUPPLY 48V-DC / 200W 29

Dimtype: non dimmable


Cutout dimension (mm): 40

modifier les dispositifs de lumière




251 70 03 01 B BOXY HONEYCOMB B

251 70 03 01 W BOXY HONEYCOMB W



251 70 03 04 B BOXY SOFTENING LENS B

251 70 03 04 W BOXY SOFTENING LENS W




251 70 03 05 B BOXY GLASS SBL B

251 70 03 05 W BOXY GLASS SBL W

COMPATIBLE COMPOSABLES

SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)

Available Colours




23358 0000 SLM26L - PROFILE

DELTALIGHT


M26L - BOXY L SOFT 93045 MDL

10735 9030 B-FBR




23358 0010 SLM26L - PROFILE 1m





23358 0020 SLM26L - PROFILE 2m





23358 0030 SLM26L - PROFILE 3m



Notes: