





M20/M26H - OBIN 93036 DIM5

30514 9335 BRBB

- AVAILABLE IN
- BLACK 30514 9335 B
 - BRUSHED ALU 30514 9335 BRA
 - BRUSHED ANTHRACITE 30514 9335 BRAT
 - BRUSHED BROWN BRONZE 30514 9335 BRBB
 - BRUSHED GOLD 30514 9335 BRG
 - BRUSHED OLD BRONZE 30514 9335 BROB
 - CREAM 30514 9335 CR
 - WHITE 30514 9335 W



 [View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	0° to 45° swiveling, 360° rotatable
INFORMATION	LENS FL-36° EXCL.LED POWER SUPPLY 48V-DC
Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	CB, ENEC
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 11,6W / CRI>90 (R9: 52) / 3000K / 1524lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	36°
LED TECHNICS (LIGHT SOURCE)	1524lm // 11,6W // 131lm/W
LED TECHNICS (LUMINAIRE)	1315lm // 13,3W // 99lm/W
Requirements	
SPY 90 TUBE	
LED POWER SUPPLY 48V-DC	
Accessories	
HONEYCOMB 75	

M20/M26H - OBIN 93036 DIM5

30514 9335 BRBB

For detailed installation instructions, please consult the manual : [30514_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION

LED power supplies		# of Fixtures
# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
5510090 300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN Dimtype: non-dimmable	7	
63114125 300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN Dimtype: non-dimmable	14	
3017298 21012 0230 LED POWER SUPPLY 48V-DC / 100W Dimtype: non-dimmable Cutout dimension (mm): 40	7	
3022392 21012 0240 LED POWER SUPPLY 48V-DC / 200W Dimtype: non-dimmable Cutout dimension (mm): 40	14	
Light altering devices		
13075 19810 0110 B HONEYCOMB 75 SINGLE USE B		

DELTALIGHT

M20/M26H - OBIN 93036 DIM5

30514 9335 BRBB

Finish your product

	19810 0170 B	SPY 90 TUBE B	☐
	19810 0170 CR	SPY 90 TUBE CR	☐
	19810 0170 DC	SPY 90 TUBE DC	☐
	19810 0170 FBR	SPY 90 TUBE FBR	☐
	19810 0170 FG	SPY 90 TUBE FG	☐
	19810 0170 GC	SPY 90 TUBE GC	☐
	19810 0170 PB	SPY 90 TUBE PB	☐
	19810 0170 W	SPY 90 TUBE W	☐




COMPATIBLE COMPOSABLES

SHIFTLINE M26H + SBL		Available Colours
	30411 9205 SHIFTLINE M26H + SBL 2m DIM5	☒ ☐
	30411 9305 SHIFTLINE M26H + SBL 2m DIM5	☒ ☐
	30412 9205 SHIFTLINE M26H + SBL 3m DIM5	☒ ☐

DELTALIGHT





M20/M26H - OBIN 93036 DIM5

30514 9335 BRBB

	30412 9305 SHIFTLINE M26H + SBL 3m DIM5	
	30413 9205 SHIFTLINE M26H + SBL 4m DIM5	
	30413 9305 SHIFTLINE M26H + SBL 4m DIM5	

SHIFTLINE M26H profile

Available Colours

	23359 0000 SLM26H - PROFILE	
	23359 0010 SLM26H - PROFILE 1m	
	23359 0020 SLM26H - PROFILE 2m	
	23359 0030 SLM26H - PROFILE 3m	

SPLITLINE M20 ST profile

Available Colours

	23397 0000 SPM20 ST - PROFILE	
	23397 0020 SPM20 ST - PROFILE 2m	

DELTALIGHT

M20/M26H - OBIN 93036 DIM5

30514 9335 BRBB




23397 0030 SPM20 ST - PROFILE 3m



SPLITLINE M20 profile


Available Colours




420 20 10 00 SPM20 - PROFILE 1m



420 20 20 00 SPM20 - PROFILE 2m



420 20 30 00 SPM20 - PROFILE 3m



23301 0000 SPM20 - PROFILE B



Notes: