





KIX II 93055

13534 9330 A

AVAILABLE IN
ALU GREY 13534 9330 A
ANTHRACITE 13534 9330 N



 [View on website](#)



General info	
LOCATION	outdoor
INSTALLATION	Wall Surface mounted
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK07
WEIGHT (KG)	1
ADJUSTABILITY	0° to 90° swiveling
INFORMATION	REFLECTOR WFL-55° INCL.LED POWER SUPPLY 350mA-DC

Electrical info	
ELECTRICAL	100-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	C


Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	55°
LED TECHNICS (LIGHT SOURCE)	787lm // 5,8W // 135lm/W
LED TECHNICS (LUMINAIRE)	689lm // 6,7W // 103lm/W

Accessories	
KAP KIX	
HONEYCOMB KIX	


For detailed installation instructions, please consult the manual : [13534_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Light altering devices



232 10 00 N KAP KIX N

☐

232 10 03 N HONEYCOMB KIX N

☐

Notes: