
DELTALIGHT




# KIX II 93055

**REFERENCE** 13534 9330 A

AVAILABLE IN
**ALU GREY** 13534 9330 A
**ANTHRACITE** 13534 9330 N




View on website

| General info | |
|---|---|
| **LOCATION** | outdoor |
| **INSTALLATION** | Wall Surface mounted |
| **INGRESS PROTECTION** | IP65 |
| **PROTECTION AGAINST MECHANICAL IMPACT** | IK07 |
| **WEIGHT (KG)** | 1 |
| **ADJUSTABILITY** | 0° to 90° swiveling |
| **INFORMATION** | REFLECTOR WFL-55°<br>INCL.LED POWER SUPPLY 350mA-DC |

| Electrical info | |
|---|---|
| **ELECTRICAL** | 100-240V / 50-60Hz |
| **CLASS** | II |
| **POWER SUPPLY** | YES |
| **DIM TYPE** | non-dimmable |
| **ENERGY CLASS** | C |

| Lightsource info | |
|---|---|
| **LIGHTSOURCE NAME** | LED |
| **LIGHTSOURCE** | LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm |
| **TM-30 VALUES** | Rf: 90 / Rg: 99 |
| **SDCM** | SDCM1 |
| **RISKGROUP** | RG1 |
| **LM80** | L90B10 > 50000 |
| **BEAMANGLE** | 55° |
| **LED TECHNICS (LIGHT SOURCE)** | 787lm // 5,8W // 135lm/W |
| **LED TECHNICS (LUMINAIRE)** | 689lm // 6,7W // 103lm/W |

**Accessories**

KAP KIX
HONEYCOMB KIX

For detailed installation instructions, please consult the manual : **13534_XXX0_HAND.pdf**


DELTALIGHT

# KIX II 93055


13534 9330 A

## FINISH YOUR SPECIFICATION

### Light altering devices




**232 10 00 N** KAP KIX N ☐




**232 10 03 N** HONEYCOMB KIX N ☐

Notes: