
DELTALIGHT




LEDS C R ST 930

REFERENCE 13611 9300 ANO

AVAILABLE IN
ALU ANODIZED 13611 9300 ANO





View on website

General info	
LOCATION	outdoor
INSTALLATION	Floor Recessed,Wall Recessed
CUTOUT SHAPE/SIZE (MM)	round - 41
RECESSED DEPTH (MM)	45
INGRESS PROTECTION	IP67
PROTECTION AGAINST MECHANICAL IMPACT	IK03
WEIGHT (KG)	0.1
ADJUSTABILITY	non adjustable
INFORMATION	EXCL.LED POWER SUPPLY 350mA-DC

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 1W / CRI>90 (R9: 60) / 3000K / 131lm
TM-30 VALUES	Rf: 91 / Rg: 101
SDCM	SDCM3
RISKGROUP	RG2
LM80	L90B10 > 150000
LED TECHNICS (LIGHT SOURCE)	131lm // 1W // 135lm/W
LED TECHNICS (LUMINAIRE)	38lm // 1,2W // 33lm/W

Requirements

LED POWER SUPPLY 350mA-DC DIM

For detailed installation instructions, please consult the manual : **13611_XXX0_HAND.pdf**


DELTALIGHT

LEDS C R ST 930

13611 9300 ANO

FINISH YOUR SPECIFICATION


LED power supplies	# of Fixtures
# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.	Min current | Max current



300 48 350 ED1 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1 — 3->14 ☐

Dimtype: 1-10V


Cutout dimension (mm): 30



300 48 350 ED5 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 — 3->14 ☐

Dimtype: DALI


Cutout dimension (mm): 45



300 48 350 MDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL — 3->14 ☐

Dimtype: non-dimmable


Cutout dimension (mm): 30



300 48 350 WDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL — 3->14 ☐

Dimtype: WDL = wireless dimmable


Cutout dimension (mm): 45



300 90 60 LED POWER SUPPLY MULTI-POWER DIM7 — 12 | 0 | 0 ☐

Dimtype: 1-10V or push button


Cutout dimension (mm): 70



300 90 61 LED POWER SUPPLY MULTI-POWER DIM6 — 16 ☐

Dimtype: mains (phase cut-off) or push button


Cutout dimension (mm): 56



300 90 63 LED POWER SUPPLY MULTI-POWER DIM9 — 26(25) ☐

Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 82



300 90 64 LED POWER SUPPLY MULTI-POWER DIM7 — 4->18(15) ☐


Dimtype: 1-10V or push button

Cutout dimension (mm): 72

DELTALIGHT


LEDS C R ST 930

13611 9300 ANO



300 90 67 LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9 3->15


Dimtype: 1-10V or DALI or push button



300 90 68 LED POWER SUPPLY MULTI-POWER DIM5 2->17(15)

Dimtype: DALI


Cutout dimension (mm): 72



300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9 8->40(39)

Dimtype: 1-10V or DALI or push button


Cutout dimension (mm): 84




300 90 91 LED POWER SUPPLY 350mA-DC / 15W 14(10)

Dimtype: non-dimmable

Cutout dimension (mm): 40




300 90 104 LED POWER SUPPLY 350mA-DC / 6W 4



300 90 112 LED POWER SUPPLY 350mA-DC / 18W 15


Dimtype: mains (phase cut-off)



300 90 124 LED POWER SUPPLY MULTI-POWER DIM7 6->17(15)

Dimtype: 1-10V or push button


Cutout dimension (mm): 55



300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5 4->17(15)

Dimtype: DALI


Cutout dimension (mm): 55



300 90 135 LED POWER SUPPLY MULTI-POWER HV 17->29

Dimtype: non-dimmable

Cutout dimension (mm): 90



21012 0010 LED POWER SUPPLY MULTI POWER 6->15


Dimtype: non-dimmable

Cutout dimension (mm): 50

DELTALIGHT

LEDS C R ST 930


13611 9300 ANO



21012 0021 LED POWER SUPPLY MULTI POWER DIM1 4->19

Dimtype: 1-10V


Cutout dimension (mm): 54



21012 0035 LED POWER SUPPLY MULTI POWER DIM5 4->19

Dimtype: DALI


Cutout dimension (mm): 54



21012 004W LED POWER SUPPLY MULTI-POWER WDL 25(25)

Dimtype: WDL = wireless dimmable


Cutout dimension (mm): 84



21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL 4->19

Dimtype: WDL = wireless dimmable


Cutout dimension (mm): 54



21012 0258 LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8 7->10

Dimtype: mains (phase cut-off)


Cutout dimension (mm): 50



21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8 10->15

Dimtype: mains (phase cut-off)


Cutout dimension (mm): 50



21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 3->15

Dimtype: mains (phase cut-off)


Cutout dimension (mm): 48



21012 0308 LED POWER SUPPLY 350mA / 7,35W DIM8 5->7

Dimtype: mains (phase cut-off)


Cutout dimension (mm): 40



21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68 2->17(15)

Dimtype: non-dimmable

Cutout dimension (mm): 60



21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 3->14

Dimtype: DALI

Cutout dimension (mm): 30

DELTALIGHT

LEDS C R ST 930

13611 9300 ANO

Notes: