



LEDS C R ST 930

13611 9300 ANO

AVAILABLE IN
ALU ANODIZED 13611 9300 ANO



 [View on website](#)



General info

LOCATION	outdoor
INSTALLATION	Floor Recessed, Wall Recessed
CUTOUT SHAPE/SIZE (MM)	round - 41
RECESSED DEPTH (MM)	45
INGRESS PROTECTION	IP67
PROTECTION AGAINST MECHANICAL IMPACT	IK03
WEIGHT (KG)	0.1
ADJUSTABILITY	non adjustable
INFORMATION	EXCL.LED POWER SUPPLY 350mA-DC

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 1W / CRI>90 (R9: 60) / 3000K / 131lm
TM-30 VALUES	rf: 92 / Rg: 99
SDCM	SDCM3
RISKGROUP	RG2
LM80	L90B10 > 150000
LED TECHNICS (LIGHT SOURCE)	131lm // 1W // 135lm/W
LED TECHNICS (LUMINAIRE)	38lm // 1,2W // 33lm/W

Requirements

LED POWER SUPPLY 350mA-DC DIM

For detailed installation instructions, please consult the manual : [13611_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION


LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




300 48 350 ED1 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1

3->14

Dimtype: 1-10V

Cutout dimension (mm): 30




300 48 350 ED5 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

3->14

Dimtype: DALI

Cutout dimension (mm): 45




300 48 350 MDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL

3->14

Dimtype: non-dimmable

Cutout dimension (mm): 30




300 48 350 WDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL

3->14

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45




300 90 60 LED POWER SUPPLY MULTI-POWER DIM7

12 | 0 | 0

Dimtype: 1-10V or push button

Cutout dimension (mm): 70




300 90 61 LED POWER SUPPLY MULTI-POWER DIM6

16

Dimtype: mains (phase cut-off) or push button

Cutout dimension (mm): 56




300 90 63 LED POWER SUPPLY MULTI-POWER DIM9

26(25)

Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 82



300 90 64 LED POWER SUPPLY MULTI-POWER DIM7

4->18(15)


Dimtype: 1-10V or push button

Cutout dimension (mm): 72

DELTALIGHT

LEDS C R ST 930

13611 9300 ANO




300 90 67

LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9

3->15

Dimtype: 1-10V or DALI or push button




300 90 68

LED POWER SUPPLY MULTI-POWER DIM5

2->17(15)

Dimtype: DALI

Cutout dimension (mm): 72




300 90 69

LED POWER SUPPLY MULTI-POWER HV DIM9

8->40(39)

Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 84




300 90 91

LED POWER SUPPLY 350mA-DC / 15W

14(10)

Dimtype: non-dimmable


Cutout dimension (mm): 40



300 90 104

LED POWER SUPPLY 350mA-DC / 6W

4




300 90 112

LED POWER SUPPLY 350mA-DC / 18W

15

Dimtype: mains (phase cut-off)




300 90 124

LED POWER SUPPLY MULTI-POWER DIM7

6->17(15)

Dimtype: 1-10V or push button

Cutout dimension (mm): 55




300 90 125

LED POWER SUPPLY MULTI-POWER MINI DIM5

4->17(15)

Dimtype: DALI

Cutout dimension (mm): 55




300 90 135

LED POWER SUPPLY MULTI-POWER HV

17->29

Dimtype: non-dimmable

Cutout dimension (mm): 90



21012 0010

LED POWER SUPPLY MULTI POWER

6->15


Dimtype: non-dimmable

Cutout dimension (mm): 50

DELTALIGHT

LEDS C R ST 930

13611 9300 ANO




21012 0021 LED POWER SUPPLY MULTI POWER DIM1

4->19

Dimtype: 1-10V

Cutout dimension (mm): 54




21012 0035 LED POWER SUPPLY MULTI POWER DIM5

4->19

Dimtype: DALI

Cutout dimension (mm): 54




21012 004W LED POWER SUPPLY MULTI-POWER WDL

25(25)

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 84




21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL

4->19

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 54




21012 0258 LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8

7->10

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 50




21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8

10->15

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 50




21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8

3->15

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 48




21012 0308 LED POWER SUPPLY 350mA / 7,35W DIM8

5->7

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 40




21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68

2->17(15)

Dimtype: non-dimmable

Cutout dimension (mm): 60



21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

3->14

Dimtype: DALI

Cutout dimension (mm): 30

DELTALIGHT

LEDS C R ST 930

13611 9300 ANO

Notes: