




SPY 52 ON TW 96545

REFERENCE 19825 9030 B

AVAILABLE IN
BLACK 19825 9030 B
FULL WHITE 19825 9030 FW
WHITE 19825 9030 W



 [View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.4
ADJUSTABILITY	0° to 90° swiveling, 355° rotatable
INFORMATION	REFLECTOR WFL-45° EXCL.LED POWER SUPPLY 500mA-DC TW - (DALI DT8) Optional REFLECTORS 20° & 30° available

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, LCA

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 9W / CRI>90 (R9: 50) / 2700K-6500K / 1087lm
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	45°
LED TECHNICS (LIGHT SOURCE)	1087lm // 9W // 121lm/W
LED TECHNICS (LUMINAIRE)	695lm // 10,4W // 67lm/W

Requirements	
SPY 52 TUBE	
LED POWER SUPPLY 500mA-DC TW	

Options	
COVERSET R 90-100	

Accessories	
HONEYCOMB 42	
SPREAD LENS 42	
LINEAR SPREAD LENS 42	
SOFTENING LENS 42	
GLASS SBL 42	

For detailed installation instructions, please consult the manual : [19825_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION






LED power supplies		# of Fixtures
# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
124 24 79	21012 0355 LED POWER SUPPLY 500mA-DC 2CH TW DIM5 Dimtype: DALI Cutout dimension (mm): 85	2
Coversets		
Ø90 2 Ø10 2	204 00 90 ANO COVERSET R 90 ANO	
	204 00 90 B COVERSET R 90 B	
	204 00 90 W COVERSET R 90 W	
Ø100 2 Ø10 2	204 00 100 ANO COVERSET R 100 ANO	
	204 00 100 B COVERSET R 100 B	
	204 00 100 W COVERSET R 100 W	

DELTALIGHT


SPY 52 ON TW 96545

19825 9030 B

Light altering devices

 13 Ø42	19810 0010 B HONEYCOMB 42 SINGLE USE B	☐
 13 Ø42	19810 0020 LINEAR SPREAD LENS 42	☐
 13 Ø42	19810 0030 SPREAD LENS 42	☐
 13 Ø42	19810 0040 SOFTENING LENS 42	☐
 13 Ø42	19810 0050 GLASS SBL 42	☐
 14 Ø42	19810 0060 B HONEYCOMB 42 DOUBLE USE B	☐

Finish your product

 40 Ø49	19810 0100 B SPY 52 TUBE B	☐
	19810 0100 FBR SPY 52 TUBE FBR	☐
	19810 0100 FG SPY 52 TUBE FG	☐
	19810 0100 GC SPY 52 TUBE GC	☐

DELTALIGHT

SPY 52 ON TW 96545

19825 9030 B

19810 0100 W SPY 52 TUBE W

☐

Replaceable reflector / lens



19810 0180 SPY 52 REFLECTOR 20°

☐

19810 0190 SPY 52 REFLECTOR 45°

☐

19810 0240 SPY 52 REFLECTOR 30°

☐

Notes: