



## MIKALINE-OH! L198 93034 MDL

30615 9320 B

AVAILABLE IN  
**BLACK** 30615 9320 B  
**GOLD COLOURED** 30615 9320 GC



 [View on website](#)



### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Ceiling Surface mounted,Ceiling Suspended,Wall Surface mounted
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	1.1
<b>ADJUSTABILITY</b>	non adjustable
<b>INFORMATION</b>	INCL.PLUG-IN-48V CABLE 11cm black EXCL.LED POWER SUPPLY 48V-DC connection max.140W (3A)

### Electrical info

<b>ELECTRICAL</b>	48V-DC
<b>CLASS</b>	III
<b>DIM TYPE</b>	MDL = 1-10V or DALI or push button
<b>ENERGY CLASS</b>	F
<b>CERTIFICATES</b>	CB, ENEC

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	3 x (LED cluster 5,2W / CRI>90 (R9: 50) / 3000K / 596lm)
<b>TM-30 VALUES</b>	Rf: 90 / Rg: 101
<b>SDCM</b>	SDCM3
<b>LM80</b>	L80 > 60000
<b>BEAMANGLE</b>	34°
<b>LED TECHNICS (LIGHT SOURCE)</b>	1788lm // 15,6W // 115lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	1413lm // 17,9W // 79lm/W

### Requirements

LED POWER SUPPLY 48V-DC (Remote)  
 DIMMABLE MODULATOR  
 POWERBOX 48V-DC PLUG-IN

### Options

MIKALINE - JUNCTION / FIXATION  
 MIKALINE - CABLE SUSPENSION  
 PLUG-IN 48V CABLE  
 CONNECTION CLIP 1 x PLUG-IN 48V  
 CEILING BASE PLUG-IN 48V

# DELTALIGHT


## MIKALINE-OH! L198 93034 MDL

30615 9320 B

For detailed installation instructions, please consult the manual : [30615\\_XXX0\\_HAND.pdf](#)


### FINISH YOUR SPECIFICATION

#### SMART 48



**300 90 011** SMART 48 MODULATOR DIM9


Dimtype: 1-10V or DALI or push button




**300 90 012** SMART 48 MODULATOR WD

Dimtype: WDL = wireless dimmable


#### Current supply



**30610 0100** PLUG-IN 48V CABLE 11cm black



**30610 0110** PLUG-IN 48V CABLE 1,5m black



**30610 0120** PLUG-IN 48V CABLE 3m black



**30610 0140 B** CONNECTION CLIP 1 x PLUG-IN 48V B

Cutout dimension (mm): 51


# DELTALIGHT

## MIKALINE-OH! L198 93034 MDL

30615 9320 B


### LED power supplies

---




**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN

Dimtype: non-dimmable



**300 89 48 240** LED POWER SUPPLY 48V-DC / 240W DIN


Dimtype: non-dimmable



**21012 0230** LED POWER SUPPLY 48V-DC / 100W

Dimtype: non-dimmable


Cutout dimension (mm): 40



**21012 0240** LED POWER SUPPLY 48V-DC / 200W

Dimtype: non-dimmable

Cutout dimension (mm): 40




**30610 0190** POWER ADAPTER 48V-DC / 60W PLUG-IN

Dimtype: non-dimmable



### Power box

---



**30610 0170 B** POWERBOX 48V-DC / 100W PLUG-IN B

Dimtype: non-dimmable



### Suspension parts

---



**30610 0080 B** MIKALINE - CABLE SUSPENSION SINGLE 1,6m B



# DELTALIGHT

## MIKALINE-OH! L198 93034 MDL

30615 9320 B

### Fixation components

---



**30610 0010 C** MIKALINE - JUNCTION 2 FLEX SET C



**30610 0020 C** MIKALINE - JUNCTION 3 FLEX C




**30610 0030 C** MIKALINE - JUNCTION 4 FLEX C



**30610 0040 C** MIKALINE - JUNCTION 2 HINGE C



**30610 0050 C** MIKALINE - FIXATION SIDE SET C




**30610 0060 B** MIKALINE - FIXATION SPACER FLEX SET B



**30610 0070 C** MIKALINE - FIXATION H/V FLEX C



**30610 0090 B** MIKALINE - FIXATION SPACER SET B



**30610 0180 B** MIKALINE - SPACER 90° 2 SET B

# DELTALIGHT

## MIKALINE-OH! L198 93034 MDL

30615 9320 B

### Ceiling bases

---



**30610 0150 B** CEILING BASE 3 x PLUG-IN 48V B



**30610 0160 B** CEILING BASE 1 x PLUG-IN 48V B



Notes: