





KIX II HP PIN 92730

13535 9220 N

AVAILABLE IN
ALU GREY 13535 9220 A
ANTHRACITE 13535 9220 N
PINE GREEN 13535 9220 PGR



 [View on website](#)



General info

LOCATION	outdoor
INSTALLATION	Floor Surface mounted
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK03
WEIGHT (KG)	1
ADJUSTABILITY	180° swiveling, 360° rotatable
INFORMATION	REFLECTOR FL-30° INCL.1 x CABLE H05 RN-F 2 x 1mm ² 2m EXCL.LED POWER SUPPLY 500mA-DC

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 16,3W / CRI>90 (R9: 60) / 2700K / 2209lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	30°
LED TECHNICS (LIGHT SOURCE)	2209lm // 16,3W // 136lm/W
LED TECHNICS (LUMINAIRE)	1807lm // 18,7W // 96lm/W

Requirements

LED POWER SUPPLY 500mA-DC DIM

Options

CBOX
 IP68 CONNECTION KIT
 IP68 CONNECTOR 3P

Accessories

KAP KIX
 HONEYCOMB KIX

DELTALIGHT

KIX II HP PIN 92730


13535 9220 N

For detailed installation instructions, please consult the manual : [13535_XXX0_HAND.pdf](#)


FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




300 48 500 ED1 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1

1

Dimtype: 1-10V

Cutout dimension (mm): 30




300 48 500 ED5 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5

1

Dimtype: DALI

Cutout dimension (mm): 45




300 48 500 MDL LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL

1

Dimtype: non-dimmable

Cutout dimension (mm): 30




300 48 500 WDL LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL

1

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45




300 90 61 LED POWER SUPPLY MULTI-POWER DIM6

1

Dimtype: mains (phase cut-off) or push button

Cutout dimension (mm): 56




300 90 63 LED POWER SUPPLY MULTI-POWER DIM9

2(2)

Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 82



300 90 64 LED POWER SUPPLY MULTI-POWER DIM7

1(0)


Dimtype: 1-10V or push button

Cutout dimension (mm): 72

DELTALIGHT

KIX II HP PIN 92730

13535 9220 N




300 90 68 LED POWER SUPPLY MULTI-POWER DIM5

1(0)

Dimtype: DALI

Cutout dimension (mm): 72




300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9

3(2)

Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 84




300 90 124 LED POWER SUPPLY MULTI-POWER DIM7

1(0)

Dimtype: 1-10V or push button

Cutout dimension (mm): 55




300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5

1(0)

Dimtype: DALI

Cutout dimension (mm): 55




300 90 135 LED POWER SUPPLY MULTI-POWER HV

2->2

Dimtype: non-dimmable

Cutout dimension (mm): 90




21012 0010 LED POWER SUPPLY MULTI POWER

1

Dimtype: non-dimmable

Cutout dimension (mm): 50




21012 0021 LED POWER SUPPLY MULTI POWER DIM1

1

Dimtype: 1-10V

Cutout dimension (mm): 54




21012 0035 LED POWER SUPPLY MULTI POWER DIM5

1

Dimtype: DALI

Cutout dimension (mm): 54




21012 004W LED POWER SUPPLY MULTI-POWER WDL

2(2)

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 84



21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL

1


Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 54

DELTALIGHT

KIX II HP PIN 92730

13535 9220 N




21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8

1

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 48




21012 0500 LED POWER SUPPLY 500mA-DC / 24W IP68

1(0)

Dimtype: non-dimmable

Cutout dimension (mm): 60




21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5

1

Dimtype: DALI


Cutout dimension (mm): 30

Waterproof connection parts



216 12 00 CBOX

Cutout dimension (mm): 142 x 142




216 12 01 IP68 CONNECTION KIT




216 12 02 IP68 CONNECTOR 3P

Light altering devices



232 10 00 N KAP KIX N



232 10 03 N HONEYCOMB KIX N

DELTALIGHT

KIX II HP PIN 92730

13535 9220 N

Notes: