




## MIKALINE-OH! L198 93034 MDL

30615 9320 GC

AVAILABLE IN  
**BLACK** 30615 9320 B  
**GOLD COLOURED** 30615 9320 GC



[View on website](#)



| General info                |                                                                                               |
|-----------------------------|-----------------------------------------------------------------------------------------------|
| LOCATION                    | indoor                                                                                        |
| INSTALLATION                | Ceiling Surface mounted,Ceiling Suspended,Wall Surface mounted                                |
| INGRESS PROTECTION          | IP20                                                                                          |
| WEIGHT (KG)                 | 1.1                                                                                           |
| ADJUSTABILITY               | non adjustable                                                                                |
| INFORMATION                 | INCL.PLUG-IN-48V CABLE 11cm black<br>EXCL.LED POWER SUPPLY 48V-DC<br>connection max.140W (3A) |
| Electrical info             |                                                                                               |
| ELECTRICAL                  | 48V-DC                                                                                        |
| CLASS                       | III                                                                                           |
| DIM TYPE                    | MDL = 1-10V or DALI or push button                                                            |
| ENERGY CLASS                | F                                                                                             |
| CERTIFICATES                | CB, ENEC                                                                                      |
| Lightsource info            |                                                                                               |
| LIGHTSOURCE NAME            | LED                                                                                           |
| LIGHTSOURCE                 | 3 x (LED cluster 5,2W / CRI>90 (R9: 50) / 3000K / 596lm)                                      |
| TM-30 VALUES                | Rf: 90 / Rg: 101                                                                              |
| SDCM                        | SDCM3                                                                                         |
| LM80                        | L80 > 60000                                                                                   |
| BEAMANGLE                   | 34°                                                                                           |
| LED TECHNICS (LIGHT SOURCE) | 1788lm // 15,6W // 115lm/W                                                                    |
| LED TECHNICS (LUMINAIRE)    | 1413lm // 17,9W // 79lm/W                                                                     |

### Requirements

LED POWER SUPPLY 48V-DC (Remote)  
 DIMMABLE MODULATOR  
 POWERBOX 48V-DC PLUG-IN


### Options

MIKALINE - JUNCTION / FIXATION  
 MIKALINE - CABLE SUSPENSION  
 PLUG-IN 48V CABLE  
 CONNECTION CLIP 1 x PLUG-IN 48V  
 CEILING BASE PLUG-IN 48V

For detailed installation instructions, please consult the manual : [30615\\_XXX0\\_HAND.pdf](#)

FINISH YOUR SPECIFICATION


SMART 48



**300 90 011** SMART 48 MODULATOR DIM9

☐

Dimtype: 1-10V or DALI or push button




**300 90 012** SMART 48 MODULATOR WD


☐

Dimtype: WDL = wireless dimmable


Current supply



**30610 0100** PLUG-IN 48V CABLE 11cm black

☐

**30610 0110** PLUG-IN 48V CABLE 1,5m black

☐

**30610 0120** PLUG-IN 48V CABLE 3m black

☐

**30610 0140 B** CONNECTION CLIP 1 x PLUG-IN 48V B

☐


Cutout dimension (mm): 51

# DELTALIGHT

## MIKALINE-OH! L198 93034 MDL


30615 9320 GC

### LED power supplies




**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN

Dimtype: non-dimmable



**300 89 48 240** LED POWER SUPPLY 48V-DC / 240W DIN


Dimtype: non-dimmable



**21012 0230** LED POWER SUPPLY 48V-DC / 100W

Dimtype: non-dimmable


Cutout dimension (mm): 40



**21012 0240** LED POWER SUPPLY 48V-DC / 200W

Dimtype: non-dimmable

Cutout dimension (mm): 40




**30610 0190** POWER ADAPTER 48V-DC / 60W PLUG-IN

Dimtype: non-dimmable



### Power box



**30610 0170 B** POWERBOX 48V-DC / 100W PLUG-IN B

Dimtype: non-dimmable



### Suspension parts



**30610 0080 B** MIKALINE - CABLE SUSPENSION SINGLE 1,6m B




# DELTALIGHT

## MIKALINE-OH! L198 93034 MDL

30615 9320 GC

### Fixation components

|                                                                                     |                                                           |                          |
|-------------------------------------------------------------------------------------|-----------------------------------------------------------|--------------------------|
|    | <b>30610 0010 C</b> MIKALINE - JUNCTION 2 FLEX SET C      | <input type="checkbox"/> |
|    | <b>30610 0020 C</b> MIKALINE - JUNCTION 3 FLEX C          | <input type="checkbox"/> |
|    | <b>30610 0030 C</b> MIKALINE - JUNCTION 4 FLEX C          | <input type="checkbox"/> |
|   | <b>30610 0040 C</b> MIKALINE - JUNCTION 2 HINGE C         | <input type="checkbox"/> |
|  | <b>30610 0050 C</b> MIKALINE - FIXATION SIDE SET C        | <input type="checkbox"/> |
|  | <b>30610 0060 B</b> MIKALINE - FIXATION SPACER FLEX SET B | <input type="checkbox"/> |
|  | <b>30610 0070 C</b> MIKALINE - FIXATION H/V FLEX C        | <input type="checkbox"/> |
|  | <b>30610 0090 B</b> MIKALINE - FIXATION SPACER SET B      | <input type="checkbox"/> |
|   | <b>30610 0180 B</b> MIKALINE - SPACER 90° 2 SET B         | <input type="checkbox"/> |

# DELTALIGHT

## MIKALINE-OH! L198 93034 MDL

30615 9320 GC

### Ceiling bases

---



**30610 0150 B** CEILING BASE 3 x PLUG-IN 48V B

☐

**30610 0160 B** CEILING BASE 1 x PLUG-IN 48V B

☐

Notes: