



BOXY R SOFT 93045 DIM8

10745 9038 B-FG

AVAILABLE IN



BLACK-BLACK 10745 9038 B-B

BLACK-FLEMISH BRONZE 10745 9038 B-FBR

BLACK-FLEMISH GOLD 10745 9038 B-FG

WHITE-BLACK 10745 9038 W-B

WHITE-WHITE 10745 9038 W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.6
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR WFL-45° INCL.DIMMABLE POWER SUPPLY 500mA-DC

Electrical info

ELECTRICAL	220-240V / 0 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	F
CERTIFICATES	LCA, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 10,2W / CRI>90 (R9: 50) / 3000K-1800K / 1038lm
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	45°
LED TECHNICS (LIGHT SOURCE)	1038lm // 10,2W // 109lm/W
LED TECHNICS (LUMINAIRE)	794lm // 11,7W // 68lm/W

Accessories

BOXY HONEYCOMB
BOXY SOFTENING LENS
BOXY GLASS SBL

For detailed installation instructions, please consult the manual : [10745_XXX8_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Light altering devices

 Ø40	 Ø45 1.5	<u>251 70 03 01 B</u> BOXY HONEYCOMB B	☐
<u>251 70 03 01 W</u> BOXY HONEYCOMB W			☐
 Ø40	 Ø45 1.5	<u>251 70 03 04 B</u> BOXY SOFTENING LENS B	☐
<u>251 70 03 04 W</u> BOXY SOFTENING LENS W			☐
 Ø40	 Ø45 1.5	<u>251 70 03 05 B</u> BOXY GLASS SBL B	☐
<u>251 70 03 05 W</u> BOXY GLASS SBL W			☐

Notes: