LASS-OH LINEAR



Lass-Oh! glides trough the room as a snake sliding through the greensward, showing off its slim cylindrical contour in combination with the miniature LED clusters hidden inside its body. Straight lines in combination with the optional shades make of Lass-Oh! a very decorative lighting solution. Nevertheless, Lass-Oh! can easily be hung in every residential, retail or office project thanks to its low-glare LED dots that are hidden away into the profile.

Specification	
Aperture:	5/16"
Installation method:	4" junction box -or- Power Box with 1/2" EMT conduit
Adjustability:	Fixed
Rating:	Damp

Performance	
CRI / TM-30 (3000K):	90 / Rf: 90 / Rg: 101
SDCM:	3
LED Maintenance:	L80>60,000h

*Power	HP
Standard Power L15:	3 x 7W
Standard Power L21:	4 x 7W
Standard Power L33:	6 x 7W

Delivered Lumens	2700K	3000K	3500K
Lass-Oh L15:	1577	1619	1686
Lass-Oh L21:	2102	2159	2248
Lass-Oh L33:	3153	3239	3371

Listing
ETL certified to US and Canadian safety standards.

Warranty
5-year limited warranty.

Ordering
ALL BOXES MUST BE FILLED IN TO CORRECTLY ORDER

Example: LSOL33-SPMD30-GC-PCNA-PBBD14-UNV

Luminaire	Shape	Length	Power	Optic	CCT	Finish	Style	Installation	Application	Controls***
LSO LASS-OH	**L** Linear	**15** 1502mm / 59 1/8" **21** 2111mm / 83 1/8" **33** 3331mm / 131 1/8"	**SP** Standard Power	**MD** Medium Spot 34°	**27** 2700K **30** 3000K **35** 3500K	**B** Black **GC** Gold Colored	**PC** Pendant, cable suspended[1]	**PRB** Round black coverplate for 4" junction box **PSB** Square black coverplate for 4" junction box	**RMT** Remote Power Supply	**D1-UNV** 0-10V dim 120-277V **D1-347** 0-10V dim 347V
								NA No accessory, utilizing 1/2" EMT install	**PBB**[2] Power Box Black	**D14-UNV** 0-10V dim 120-277V / FE ELV dim 120V


1 Length 15 & 21 have 2 suspension points; Length 33 has 3 suspension points.
2 Power Box not offered in Length 15.
*** Contact factory for Dali, DMX, or other dimming options.


Related Products


Lass-Oh, Dot.Com, Inform L

Finish Options

LASS-OH L15 HP **LASS-OH L21 HP** **LASS-OH L33 HP**









BLACK


GOLD COLORED

Accessories





JIHA! R - 24814 0030 B


BLACK


ALT VIEW


INSTALLED ON BLACK


INSTALLED ON GOLD



JIHA! R - 24814 0020 B


BLACK



ALT VIEW


INSTALLED ON BLACK


INSTALLED ON GOLD

Photometric Data

LASS-OH




MD 34°

Installation Options


REMOTE DRIVER (With Controls D1)

A: 8″ x **B:** 2″-3/16 x **C:** 4″-1/4
A: 203mm x **B:** 72mm x **C:** 108mm

- For Remote application
- ETL Listed
- Damp rated




PR - COVERPLATE R 104 B




BLACK
Requires 4" junction box

PS - COVERPLATE 3 103 B



BLACK
Requires 4" junction box

PBB - POWER BOX





BLACK

Driver Options

D1

• Dimming Control	0-10V
• Dimming Range	1-100%
• Dim to off	yes at 0.7mA
• Power Factor @ Full Load	>0.9
• Efficiency @ Full Load	≥87
• THD @ Full Load	<20%
• Title 24 Compliant	

Dimmer Compatibility

- Leviton IP710-DLZ
- Lutron DVTV-XX
- WattStopper ADF-120277
- Synergy Lighting Controls ISD BC

D14

• Dimming Control	Phase Control or -10V
• Dimming Range	1-100%
• Dim to off	yes
• Power Factor @ Full Load	>0.9
• Efficiency @ Full Load	≥90
• THD @ Full Load	<20%

Dimmer Compatibility Phase

- Leviton IP1106-1LZ / 6631-2
- Leviton DVELV-303P / MAELV-600

Dimmer Compatibility 0-10V

- Leviton IP710-DLZ
- Leviton DVTV-XX

As technology changes, please use information above as guidance. For most recent updated information please contact factory. Specifications subject to change without notice.