



MONTUR M LED 927

232 212 92 B

AVAILABLE IN



ALU GREY 232 212 92 A

BLACK 232 212 92 B

FLEMISH BRONZE OUTDOOR 232 212 92 FBRX

ANTHRACITE 232 212 92 N

WHITE 232 212 92 W



[View on website](#)



General info

LOCATION	indoor-outdoor
INSTALLATION	Ceiling Surface mounted, Wall Surface mounted
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK07
WEIGHT (KG)	2.6
ADJUSTABILITY	non adjustable
INFORMATION	INCL.GLASS OPAL INCL.LED POWER SUPPLY 350mA-DC

Electrical info

ELECTRICAL	100-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, LCA, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 6,3W / CRI>90 (R9: 50) / 2700K / 877lm
TM-30 VALUES	Rf: 93 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	877lm // 6,3W // 139lm/W
LED TECHNICS (LUMINAIRE)	435lm // 7,2W // 60lm/W

For detailed installation instructions, please consult the manual : [232 212_XX_HAND.pdf](#)

DELTALIGHT

MONTUR M LED 927

232 212 92 B

Notes: