
DELTALIGHT




# SL19 - SPY 20 L 92730 DIM5

**REFERENCE** 27029 9225 GC

AVAILABLE IN
**BLACK** 27029 9225 B
**FLEMISH BRONZE** 27029 9225 FBR
**FLEMISH GOLD** 27029 9225 FG
**GOLD COLOURED** 27029 9225 GC
**WHITE** 27029 9225 W




View on website

| General info | |
|---|---|
| **LOCATION** | indoor |
| **INSTALLATION** | Low voltage systems Low voltage system mounted |
| **INGRESS PROTECTION** | IP20 |
| **WEIGHT (KG)** | 0.1 |
| **ADJUSTABILITY** | 0° to 90° swiveling, 355° rotatable |
| **INFORMATION** | REFLECTOR FL-30°<br>EXCL.LED POWER SUPPLY 48V-DC<br>SPY 20 TUBE B included |

| Electrical info | |
|---|---|
| **ELECTRICAL** | 48V-DC |
| **CLASS** | III |
| **DIM TYPE** | DALI |
| **ENERGY CLASS** | E |
| **CERTIFICATES** | CB, ENEC |

| Lightsource info | |
|---|---|
| **LIGHTSOURCE NAME** | LED |
| **LIGHTSOURCE** | LED array 2W / CRI>90 (R9: 55) / 2700K / 220lm |
| **TM-30 VALUES** | Rf: 91 / Rg: 99 |
| **SDCM** | SDCM3 |
| **RISKGROUP** | RG2 |
| **LM80** | L90B10 > 150000 |
| **BEAMANGLE** | 30° |
| **LED TECHNICS (LIGHT SOURCE)** | 220lm // 2W // 110lm/W |
| **LED TECHNICS (LUMINAIRE)** | 166lm // 2,3W // 72lm/W |

**Requirements**

LED POWER SUPPLY 48V-DC

For detailed installation instructions, please consult the manual : **27029_XXX5_HAND.pdf**

DELTALIGHT

# SL19 - SPY 20 L 92730 DIM5

27029 9225 GC


## FINISH YOUR SPECIFICATION

### LED power supplies

### # of Fixtures


**Min current | Max current**

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.





**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN — 37

**Dimtype: non-dimmable**




**300 89 48 240** LED POWER SUPPLY 48V-DC / 240W DIN — 90


**Dimtype: non-dimmable**




**21012 0230** LED POWER SUPPLY 48V-DC / 100W — 37

**Dimtype: non-dimmable**

**Cutout dimension (mm): 40**




**21012 0240** LED POWER SUPPLY 48V-DC / 200W — 75


**Dimtype: non-dimmable**

**Cutout dimension (mm): 40**


## COMPATIBLE COMPOSABLES

### SHIFTLINE 19 profile

### Available Colours




**27011 0050** SL19 - PROFILE 2m




**27011 0060** SL19 - PROFILE 3m

Notes:

## SL19 - SPY 20 L 92730 DIM5

27029 9225 GC