



ENTERO RD-M TRIMLESS 93045



28430 9330 B

AVAILABLE IN

NOIR 28430 9330 B

ENTIÈREMENT BLANC 28430 9330 FW

COULEUR OR 28430 9330 GC



[View on website](#)



General info

LOCATION	interieur
INSTALLATION	Plafond Encastré
CUTOUT SHAPE/SIZE (MM)	circulaire - Ø KIT
RECESSED DEPTH (MM)	135
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.4
ADJUSTABILITY	0° à 30° inclinable, 355° rotatif
INFORMATION	REFLECTOR WFL-45° EXCLLED POWER SUPPLY 350-700mA-DC Optional REFLECTORS 18° & 30° available

Electrical info

CLASS	III
DIM TYPE	selon le type d'alimentation externe
ENERGY CLASS	E
CERTIFICATION	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 11,6-25W / CRI>90 (R9: 52) / 3000K / 1524-2811lm
RVALUES	rf: 90 / Rg: 99
SDMC	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	45°
LED TECHNICS (LIGHT SOURCE)	2811lm // 25W // 112lm/W
LED TECHNICS (LUMINAIRE)	2048lm // 28,8W // 71lm/W

Remarks

Max.500mA when using 1 accessory; max 450mA when using 2 accessories

Requirements

MOUNTING KIT ENTERO ROUND M

LED POWER SUPPLY 350 / 500 / 700mA-DC DIM (Remote)

Accessories

ENTERO M HONEYCOMB

ENTERO M LINEAR SPREAD LENS

ENTERO M SPREAD LENS

ENTERO M SOFTENING LENS

ENTERO M GLASS SBL

ENTERO RD-M TRIMLESS 93045

28430 9330 B


For detailed installation instructions, please consult the manual : [28430_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 System ceiling	 28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.	Required
 Plasterboard	 28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.	Required
 Stucanet	 28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.	Required
 Concrete + plaster	 28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.	Required
 Lintel + plaster	 28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.	Required
 Hollow-core slab + plaster	 28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.	Required
 Stretched ceiling	 28400 0140 - MOUNTING KIT ENTERO RD-M WSC	Required
	 28400 0080 - MOUNTING KIT ENTERO RD-M CSC	Required

FINISH YOUR SPECIFICATION

les batteries de secours

	21032 0270 B EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B	☐
	21032 0270 W EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W	☐

les alimentations led

of Fixtures

 web2print_power_supply_info_box	Min current Max current
---	---------------------------









ENTERO RD-M TRIMLESS 93045

28430 9330 B

	300 48 350 ED1	LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1	1	☐
	Dimtype: 1 à 10 V			
	Cutout dimension (mm): 30			
	300 48 350 ED5	LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5	1	☐
	Dimtype: DALI			
	Cutout dimension (mm): 45			
	300 48 350 MDL	LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL	1	☐
	Dimtype: non dimmable			
	Cutout dimension (mm): 30			
	300 48 350 WDL	LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL	1	☐
	Dimtype: WDL = dimmable sans fil			
	Cutout dimension (mm): 45			
	300 48 500 ED1	LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1	1	☐
	Dimtype: 1 à 10 V			
	Cutout dimension (mm): 30			
	300 48 500 ED5	LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5	1	☐
	Dimtype: DALI			
	Cutout dimension (mm): 45			
	300 48 500 MDL	LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL	1	☐
	Dimtype: non dimmable			
	Cutout dimension (mm): 30			
	300 48 500 WDL	LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL	1	☐
	Dimtype: WDL = dimmable sans fil			
	Cutout dimension (mm): 45			
	300 48 700 ED1	LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM1	1	☐
	Dimtype: 1 à 10 V			
	Cutout dimension (mm): 30			
	300 48 700 ED5	LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM5	1	☐
	Dimtype: DALI			
	Cutout dimension (mm): 45			











ENTERO RD-M TRIMLESS 93045

28430 9330 B

	300 48 700 MDL LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W MDL	1	☐
	Dimtype: non dimmable Cutout dimension (mm): 30		
	300 48 700 WDL LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W WDL	1	☐
	Dimtype: WDL = dimmable sans fil Cutout dimension (mm): 45		
	300 90 61 LED POWER SUPPLY MULTI-POWER DIM6	1 1 1	☐
	Dimtype: fin de phase ou bouton poussoir Cutout dimension (mm): 56		
	300 90 63 LED POWER SUPPLY MULTI-POWER DIM9	2(2) 2(2) 2(1)	☐
	Dimtype: 1 à 10 V ou DALI ou bouton poussoir Cutout dimension (mm): 82		
	300 90 64 LED POWER SUPPLY MULTI-POWER DIM7	1(1) 1(0) 1(0)	☐
	Dimtype: 1 à 10 V ou bouton poussoir Cutout dimension (mm): 72		
	300 90 67 LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9	1 - 1	☐
	Dimtype: 1 à 10 V ou DALI ou bouton poussoir		
	300 90 68 LED POWER SUPPLY MULTI-POWER DIM5	1(1) 1(0) 1(0)	☐
	Dimtype: DALI Cutout dimension (mm): 72		
	300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9	3(3) 3(2) 2(1)	☐
	Dimtype: 1 à 10 V ou DALI ou bouton poussoir Cutout dimension (mm): 84		
	300 90 124 LED POWER SUPPLY MULTI-POWER DIM7	1(1) 1(0) 0	☐
	Dimtype: 1 à 10 V ou bouton poussoir Cutout dimension (mm): 55		
	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5	1(1) 1(0) 0	☐
	Dimtype: DALI Cutout dimension (mm): 55		

ENTERO RD-M TRIMLESS 93045




28430 9330 B

	300 90 135 LED POWER SUPPLY MULTI-POWER HV Dimtype: non dimmable Cutout dimension (mm): 90	2->2 2 2	☐
	21012 0010 LED POWER SUPPLY MULTI POWER Dimtype: non dimmable Cutout dimension (mm): 50	1 1 1	☐
	21012 0021 LED POWER SUPPLY MULTI POWER DIM1 Dimtype: 1 à 10 V Cutout dimension (mm): 54	1 1 1	☐
	21012 0035 LED POWER SUPPLY MULTI POWER DIM5 Dimtype: DALI Cutout dimension (mm): 54	1 1 1	☐
	21012 004W LED POWER SUPPLY MULTI-POWER WDL Dimtype: WDL = dimmable sans fil Cutout dimension (mm): 84	2(2) 2(2) 2(1)	☐
	21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL Dimtype: WDL = dimmable sans fil Cutout dimension (mm): 54	1 1 1	☐
	21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8 Dimtype: fin de phase Cutout dimension (mm): 50	1	☐
	21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8 Dimtype: fin de phase Cutout dimension (mm): 55	1 1	☐
	21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 Dimtype: fin de phase Cutout dimension (mm): 48	1 1 0	☐
	21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68 Dimtype: non dimmable Cutout dimension (mm): 60	1(1)	☐


DELTALIGHT

ENTERO RD-M TRIMLESS 93045


28430 9330 B

	<u>21012 0490</u> LED POWER SUPPLY 700mA-DC / 30W IP68	1(0) ☐
Dimtype: non dimmable		
Cutout dimension (mm): 60		
	<u>21012 0500</u> LED POWER SUPPLY 500mA-DC / 24W IP68	1(0) ☐
Dimtype: non dimmable		
Cutout dimension (mm): 60		
	<u>21032 0295</u> LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5	1 ☐
Dimtype: DALI		
Cutout dimension (mm): 30		
	<u>21032 0305</u> LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5	1 ☐
Dimtype: DALI		
Cutout dimension (mm): 30		
	<u>21032 0315</u> LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM5	1 ☐
Dimtype: DALI		
Cutout dimension (mm): 30		

kit de montage

	<u>28400 0020</u> MOUNTING KIT ENTERO RD-M O.F.A.	☐
Cutout dimension (mm): 127		

kit de montage plafond tendu

	<u>28400 0080</u> MOUNTING KIT ENTERO RD-M CSC	☐
	<u>28400 0140</u> MOUNTING KIT ENTERO RD-M WSC	☐

DELTALIGHT

ENTERO RD-M TRIMLESS 93045

28430 9330 B

modifier les dispositifs de lumière

	28500 0070 ENTERO M LINEAR SPREAD LENS	☐
	28500 0080 ENTERO M SPREAD LENS	☐
	28500 0090 ENTERO M SOFTENING LENS	☐
	28500 0100 ENTERO M GLASS SBL	☐
	28500 0110 B ENTERO M HONEYCOMB SINGLE USE B	☐
	28500 0120 B ENTERO M HONEYCOMB DOUBLE USE B	☐

Réflecteur / lentille remplaçable

	24611 0220 SPY 66 REFLECTOR 18°	☐
	24611 0230 SPY 66 REFLECTOR 30°	☐

DELTALIGHT

ENTERO RD-M TRIMLESS 93045

28430 9330 B



24611 0240 SPY 66 REFLECTOR 45°



Notes: