



M20/M26H - OCTAV 27 92730 DIM5

29014 9225 GC

AVAILABLE IN



BLACK 29014 9225 B

FLEMISH BRONZE 29014 9225 FBR

FLEMISH GOLD 29014 9225 FG

GOLD COLOURED 29014 9225 GC

WHITE 29014 9225 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 85° swiveling, 355° rotatable
INFORMATION	REFLECTOR FL-30° EXCLLED POWER SUPPLY 48V-DC SPY 27 L TUBE B included

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 60) / 2700K / 753lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUPE	RG1
LM80	L90B10 > 50000
BEAMANGLE	30°
LED TECHNICS (LIGHT SOURCE)	753lm // 5,8W // 129lm/W
LED TECHNICS (LUMINAIRE)	276lm // 6,7W // 41lm/W

Remarks

Take a look at our [MAGNETIC PROFILES movie](#)

Requirements





LED POWER SUPPLY 48V-DC

For detailed installation instructions, please consult the manual : [29014_XXX5_HAND.pdf](#)


M20/M26H - OCTAV 27 92730 DIM5

29014 9225 GC

FINISH YOUR SPECIFICATION

LED power supplies		# of Fixtures
 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
 300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN Dimtype: non-dimmable	15	
 300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN Dimtype: non-dimmable	36	
 21012 0230 LED POWER SUPPLY 48V-DC / 100W Dimtype: non-dimmable Cutout dimension (mm): 40	15	
 21012 0240 LED POWER SUPPLY 48V-DC / 200W Dimtype: non-dimmable Cutout dimension (mm): 40	30	



COMPATIBLE COMPOSABLES

SHIFTLINE M26H + SBL	Available Colours
 30411 9205 SHIFTLINE M26H + SBL 2m DIM5	
 30411 9305 SHIFTLINE M26H + SBL 2m DIM5	
 30412 9205 SHIFTLINE M26H + SBL 3m DIM5	

DELTALIGHT




M20/M26H - OCTAV 27 92730 DIM5

29014 9225 GC

	30412 9305 SHIFTLINE M26H + SBL 3m DIM5	 
	30413 9205 SHIFTLINE M26H + SBL 4m DIM5	 
	30413 9305 SHIFTLINE M26H + SBL 4m DIM5	 

SHIFTLINE M26H profile

Available Colours

	23359 0000 SLM26H - PROFILE	 
	23359 0010 SLM26H - PROFILE 1m	 
	23359 0020 SLM26H - PROFILE 2m	           
	23359 0030 SLM26H - PROFILE 3m	           

SPLITLINE M20 ST profile

Available Colours

	23397 0000 SPM20 ST - PROFILE	 
	23397 0020 SPM20 ST - PROFILE 2m	 

DELTALIGHT

M20/M26H - OCTAV 27 92730 DIM5

29014 9225 GC



23397 0030 SPM20 ST - PROFILE 3m



SPLITLINE M20 profile

Available Colours



420 20 10 00 SPM20 - PROFILE 1m



420 20 20 00 SPM20 - PROFILE 2m



420 20 30 00 SPM20 - PROFILE 3m



23301 0000 SPM20 - PROFILE B



Notes: