
DELTALIGHT




SPY 52 ON 1 92745 DIM8

REFERENCE 19826 9238 B-B

AVAILABLE IN
BLACK-BLACK 19826 9238 B-B
FULL WHITE 19826 9238 FW
WHITE-WHITE 19826 9238 W-W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.6
ADJUSTABILITY	0° to 90° swiveling, 355° rotatable
INFORMATION	REFLECTOR WFL-45° INCL.DIMMABLE LED POWER SUPPLY 350/500mA-DC Current selection via jumper on power supply Optional REFLECTORS 20° & 30° available

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	@500mA: LED array 8,6W / CRI>90 (R9: 60) / 2700K / 1041lm Or @350mA: LED array 5,8W / CRI>90 (R9: 60) / 2700K / 753lm
TM-30 VALUES	@500mA: Rf: 89 / Rg: 100 @350mA: Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	45°
LED TECHNICS (LIGHT SOURCE)	@500mA: 1041lm // 8,6W // 121lm/W Or @350mA: 753lm // 5,8W // 129lm/W
LED TECHNICS (LUMINAIRE)	@500mA: 666lm // 10W // 67lm/W Or @350mA: 482lm // 7W // 72lm/W

Requirements

SPY 52 TUBE

Accessories

HONEYCOMB 42
SPREAD LENS 42

DELTALIGHT

SPY 52 ON 1 92745 DIM8


19826 9238 B-B

LINEAR SPREAD LENS 42
SOFTENING LENS 42
GLASS SBL 42


For detailed installation instructions, please consult the manual : **19826_XXX8_HAND.pdf**

FINISH YOUR SPECIFICATION


Light altering devices



19810 0010 B HONEYCOMB 42 SINGLE USE B ☐




19810 0020 LINEAR SPREAD LENS 42 ☐




19810 0030 SPREAD LENS 42 ☐



19810 0040 SOFTENING LENS 42 ☐



19810 0050 GLASS SBL 42 ☐



19810 0060 B HONEYCOMB 42 DOUBLE USE B ☐

DELTALIGHT

SPY 52 ON 1 92745 DIM8

19826 9238 B-B

Finish your product



19810 0100 B SPY 52 TUBE B ☐

19810 0100 FBR SPY 52 TUBE FBR ☐

19810 0100 FG SPY 52 TUBE FG ☐

19810 0100 GC SPY 52 TUBE GC ☐

19810 0100 W SPY 52 TUBE W ☐


Replaceable reflector / lens



19810 0180 SPY 52 REFLECTOR 20° ☐



19810 0190 SPY 52 REFLECTOR 45° ☐



19810 0240 SPY 52 REFLECTOR 30° ☐

Notes: