





HALOSCAN ST HP 92714

REFERENCE 23114 9210 B

AVAILABLE IN  
**BLACK** 23114 9210 B  
**WHITE** 23114 9210 W



 [View on website](#)



| General info                       |                                               |
|------------------------------------|-----------------------------------------------|
| LOCATION                           | indoor                                        |
| INSTALLATION                       | Ceiling Recessed                              |
| CUTOUT SHAPE/SIZE (MM)             | round - 70                                    |
| RECESSED DEPTH (MM)                | 55                                            |
| THICKNESS OF MOUNTING SURFACE (MM) | min.1                                         |
| INGRESS PROTECTION                 | IP20                                          |
| WEIGHT (KG)                        | 0.3                                           |
| ADJUSTABILITY                      | 0° to 45° swiveling, 355° rotatable           |
| INFORMATION                        | LENS SP-14°<br>EXCL.LED POWER SUPPLY 350mA-DC |

| Electrical info |                           |
|-----------------|---------------------------|
| CLASS           | III                       |
| DIM TYPE        | depending on power supply |
| ENERGY CLASS    | D                         |
| CERTIFICATES    | CB, ENEC                  |

| Lightsource info            |                                                    |
|-----------------------------|----------------------------------------------------|
| LIGHTSOURCE NAME            | LED                                                |
| LIGHTSOURCE                 | LED array 11,6W / CRI>90 (R9: 60) / 2700K / 1458lm |
| TM-30 VALUES                | Rf: 89 / Rg: 100                                   |
| SDCM                        | SDCM1                                              |
| RISKGROUP                   | RG1                                                |
| LM80                        | L90B10 > 50000                                     |
| BEAMANGLE                   | 14°                                                |
| LED TECHNICS (LIGHT SOURCE) | 1458lm // 11,6W // 125lm/W                         |
| LED TECHNICS (LUMINAIRE)    | 1185lm // 13,3W // 89lm/W                          |

| Requirements                  |
|-------------------------------|
| LED POWER SUPPLY 350mA-DC DIM |

| Accessories                 |
|-----------------------------|
| HALOSCAN HONEYCOMB          |
| HALOSCAN LINEAR SPREAD LENS |


For detailed installation instructions, please consult the manual : [23114\\_XXX0\\_HAND.pdf](#)

CEILING COMPATIBILITY

| Ceiling Type                                                                                                  | Mounting Kit |
|---------------------------------------------------------------------------------------------------------------|--------------|
|  System ceiling               | -            |
|  Plasterboard                 | -            |
|  Wood                         | -            |
|  Concrete                     | -            |
|  Concrete + plaster           | -            |
|  Lintel + plaster             | -            |
|  Hollow-core slab + plaster | -            |
|  Stretched ceiling          | -            |

FINISH YOUR SPECIFICATION

Emergency units

|                                                                                    |                                                                     |                          |
|------------------------------------------------------------------------------------|---------------------------------------------------------------------|--------------------------|
|  | <b>21032 0270 B</b> EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B | <input type="checkbox"/> |
|                                                                                    | <b>21032 0270 W</b> EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W | <input type="checkbox"/> |

LED power supplies











# of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current











HALOSCAN ST HP 92714

23114 9210 B

|                                                                                    |                                                                          |      |                          |
|------------------------------------------------------------------------------------|--------------------------------------------------------------------------|------|--------------------------|
|    | <b>300 48 350 ED1</b> LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1 | 1    | <input type="checkbox"/> |
|                                                                                    | Dimtype: 1-10V                                                           |      |                          |
|                                                                                    | Cutout dimension (mm): 30                                                |      |                          |
|    | <b>300 48 350 ED5</b> LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 | 1    | <input type="checkbox"/> |
|                                                                                    | Dimtype: DALI                                                            |      |                          |
|                                                                                    | Cutout dimension (mm): 45                                                |      |                          |
|    | <b>300 48 350 MDL</b> LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL  | 1    | <input type="checkbox"/> |
|                                                                                    | Dimtype: non-dimmable                                                    |      |                          |
|                                                                                    | Cutout dimension (mm): 30                                                |      |                          |
|    | <b>300 48 350 WDL</b> LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL  | 1    | <input type="checkbox"/> |
|                                                                                    | Dimtype: WDL = wireless dimmable                                         |      |                          |
|                                                                                    | Cutout dimension (mm): 45                                                |      |                          |
|  | <b>300 90 61</b> LED POWER SUPPLY MULTI-POWER DIM6                       | 1    | <input type="checkbox"/> |
|                                                                                    | Dimtype: mains (phase cut-off) or push button                            |      |                          |
|                                                                                    | Cutout dimension (mm): 56                                                |      |                          |
|  | <b>300 90 63</b> LED POWER SUPPLY MULTI-POWER DIM9                       | 2(2) | <input type="checkbox"/> |
|                                                                                    | Dimtype: 1-10V or DALI or push button                                    |      |                          |
|                                                                                    | Cutout dimension (mm): 82                                                |      |                          |
|  | <b>300 90 64</b> LED POWER SUPPLY MULTI-POWER DIM7                       | 1(1) | <input type="checkbox"/> |
|                                                                                    | Dimtype: 1-10V or push button                                            |      |                          |
|                                                                                    | Cutout dimension (mm): 72                                                |      |                          |
|  | <b>300 90 67</b> LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9    | 1    | <input type="checkbox"/> |
|                                                                                    | Dimtype: 1-10V or DALI or push button                                    |      |                          |
|  | <b>300 90 68</b> LED POWER SUPPLY MULTI-POWER DIM5                       | 1(1) | <input type="checkbox"/> |
|                                                                                    | Dimtype: DALI                                                            |      |                          |
|                                                                                    | Cutout dimension (mm): 72                                                |      |                          |
|  | <b>300 90 69</b> LED POWER SUPPLY MULTI-POWER HV DIM9                    | 3(3) | <input type="checkbox"/> |
|                                                                                    | Dimtype: 1-10V or DALI or push button                                    |      |                          |
|                                                                                    | Cutout dimension (mm): 84                                                |      |                          |

HALOSCAN ST HP 92714



23114 9210 B

|                                                                                    |                                                                                                                                             |                               |
|------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|
|    | <b>300 90 124</b><br>LED POWER SUPPLY MULTI-POWER DIM7<br><br>Dimtype: 1-10V or push button<br><br>Cutout dimension (mm): 55                | 1(1) <input type="checkbox"/> |
|    | <b>300 90 125</b><br>LED POWER SUPPLY MULTI-POWER MINI DIM5<br><br>Dimtype: DALI<br><br>Cutout dimension (mm): 55                           | 1(1) <input type="checkbox"/> |
|    | <b>300 90 135</b><br>LED POWER SUPPLY MULTI-POWER HV<br><br>Dimtype: non-dimmable<br><br>Cutout dimension (mm): 90                          | 2->2 <input type="checkbox"/> |
|    | <b>21012 0010</b><br>LED POWER SUPPLY MULTI POWER<br><br>Dimtype: non-dimmable<br><br>Cutout dimension (mm): 50                             | 1 <input type="checkbox"/>    |
|  | <b>21012 0021</b><br>LED POWER SUPPLY MULTI POWER DIM1<br><br>Dimtype: 1-10V<br><br>Cutout dimension (mm): 54                               | 1 <input type="checkbox"/>    |
|  | <b>21012 0035</b><br>LED POWER SUPPLY MULTI POWER DIM5<br><br>Dimtype: DALI<br><br>Cutout dimension (mm): 54                                | 1 <input type="checkbox"/>    |
|  | <b>21012 004W</b><br>LED POWER SUPPLY MULTI-POWER WDL<br><br>Dimtype: WDL = wireless dimmable<br><br>Cutout dimension (mm): 84              | 2(2) <input type="checkbox"/> |
|  | <b>21012 005W</b><br>LED POWER SUPPLY MULTI-POWER COMPACT WDL<br><br>Dimtype: WDL = wireless dimmable<br><br>Cutout dimension (mm): 54      | 1 <input type="checkbox"/>    |
|  | <b>21012 0268</b><br>LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8<br><br>Dimtype: mains (phase cut-off)<br><br>Cutout dimension (mm): 50 | 1 <input type="checkbox"/>    |
|  | <b>21012 0298</b><br>LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8<br><br>Dimtype: mains (phase cut-off)<br><br>Cutout dimension (mm): 48 | 1 <input type="checkbox"/>    |



# DELTALIGHT

## HALOSCAN ST HP 92714

23114 9210 B

|                                                                                   |                                                                      |      |                          |
|-----------------------------------------------------------------------------------|----------------------------------------------------------------------|------|--------------------------|
|  | <b>21012 0480</b> LED POWER SUPPLY 350mA-DC / 17W IP68               | 1(1) | <input type="checkbox"/> |
| Dimtype: non-dimmable                                                             |                                                                      |      |                          |
| Cutout dimension (mm): 60                                                         |                                                                      |      |                          |
|   | <b>21032 0295</b> LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 | 1    | <input type="checkbox"/> |
| Dimtype: DALI                                                                     |                                                                      |      |                          |
| Cutout dimension (mm): 30                                                         |                                                                      |      |                          |

### Light altering devices

|                                                                                    |                                               |                          |
|------------------------------------------------------------------------------------|-----------------------------------------------|--------------------------|
|    | <b>23110 0040</b> HALOSCAN LINEAR SPREAD LENS | <input type="checkbox"/> |
|  | <b>23110 0050 B</b> HALOSCAN HONEYCOMB B      | <input type="checkbox"/> |

Notes: