DELTALIGHT



OVIO 39 ON 92735

REFERENCE 40111 9240 W

AVAILABLE IN
BLACK BRONZE 40111 9240 BBR
BRUSHED ANTHRACITE 40111 9240 BRAT
WHITE 40111 9240 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 85° swiveling, 355° rotatable

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	F

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 60) / 2700K / 974lm
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	35°
LED TECHNICS (LIGHT SOURCE)	974lm // 8,6W // 113lm/W
LED TECHNICS (LUMINAIRE)	746lm // 10W // 75lm/W

Requirements

LED POWER SUPPLY 350/500mA

Accessories

HONEYCOMB 39
SOFTENING LENS 39
SANDBLASTED LENS 39
LINEAR SPREAD LENS 39

For detailed installation instructions, please consult the manual : **40111_XXX0_HAND.pdf**

DELTALIGHT

OVIO 39 ON 92735

40111 9240 W

FINISH YOUR SPECIFICATION

LED power supplies	# of Fixtures
# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.	Min current | Max current
 **300 90 63** LED POWER SUPPLY MULTI-POWER DIM9 **Dimtype: 1-10V or DALI or push button** **Cutout dimension (mm): 82**	1 -> 4 (4) | 1 -> 4 (4) ☐
 **300 90 69** LED POWER SUPPLY MULTI-POWER HV DIM9 **Dimtype: 1-10V or DALI or push button** **Cutout dimension (mm): 84**	2 -> 6 (6) | 1 -> 6 (4) ☐
 **300 90 124** LED POWER SUPPLY MULTI-POWER DIM7 **Dimtype: 1-10V or push button** **Cutout dimension (mm): 55**	1 -> 2 (2) | 1 -> 2 (1) ☐
 **300 90 125** LED POWER SUPPLY MULTI-POWER MINI DIM5 **Dimtype: DALI** **Cutout dimension (mm): 55**	1 -> 2 (2) | 1 -> 2 (1) ☐
 **21012 0010** LED POWER SUPPLY MULTI POWER **Dimtype: non-dimmable** **Cutout dimension (mm): 50**	1 -> 2 | 1 -> 2 ☐
 **21012 005W** LED POWER SUPPLY MULTI-POWER COMPACT WDL **Dimtype: WDL = wireless dimmable** **Cutout dimension (mm): 54**	1 -> 3 | 1 -> 3 ☐
 **21012 0298** LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 **Dimtype: mains (phase cut-off)** **Cutout dimension (mm): 48**	1 -> 2 | 1 -> 2 ☐
 **21012 0408** LED POWER SUPPLY 120V - 500mA-DC / 24W DIM8 **Dimtype: mains (phase cut-off)** **Cutout dimension (mm): 55**	- | 2 -> 2 (2) ☐

DELTALIGHT

OVIO 39 ON 92735

40111 9240 W



21012 0515 LED POWER SUPPLY MULTI POWER DIM5 — 1 -> 1 (1) | 1 -> 1 (1)

Dimtype: DALI

Cutout dimension (mm): 55



21012 0595 LED POWER SUPPLY 500mA-DC 10W DIM5 — - | 1 -> 1

Dimtype: DALI

Cutout dimension (mm): 35

Light altering devices

32210 0210 SOFTENING LENS 39

32210 0220 SANDBLASTED LENS 39

32210 0230 LINEAR SPREAD LENS 39



32210 0240 HONEYCOMB 39

Notes: