DELTALIGHT



DEEP RINGO HE 93020

REFERENCE 19440 9320 BRCU

AVAILABLE IN
NOIR 19440 9320 B
ALU BROSSÉ 19440 9320 BRA
ANTHRACITE BROSSÉ 19440 9320 BRAT
BRONZE BRUN BROSSÉ 19440 9320 BRBB
CUIVRE BROSSÉ 19440 9320 BRCU
OR BROSSÉ 19440 9320 BRG
BRONZE VIEUX BROSSÉ 19440 9320 BROB
CRÈME 19440 9320 CR
FLEMISH BRONZE 19440 9320 FBR
FLEMISH GOLD 19440 9320 FG
COULEUR OR 19440 9320 GC
NOIR PIANO 19440 9320 PB
BLANC 19440 9320 W





View on website

General info	
LOCATION	interieur
INSTALLATION	Plafond Encastré
CUTOUT SHAPE/SIZE (MM)	circulaire - 76
RECESSED DEPTH (MM)	90
THICKNESS OF MOUNTING SURFACE (MM)	min.5
INGRESS PROTECTION	IP43/20
WEIGHT (KG)	0.2
ADJUSTABILITY	non réglable
INFORMATION	LENS FL-20° EXCL.LED POWER SUPPLY 350mA-DC

Electrical info	
CLASS	III
DIM TYPE	selon le type d'alimentation externe
ENERGY CLASS	D
CERTIFICATION	EPD, LCA

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 6W / CRI>90 (R9: 50) / 3000K / 945lm
SDMC	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	945lm // 6W // 157lm/W
LED TECHNICS (LUMINAIRE)	808lm // 7W // 117lm/W

Remarks

High Efficacy : > 100lm/W

Requirements

LED POWER SUPPLY 350mA-DC DIM

DELTALIGHT

DEEP RINGO HE 93020

19440 9320 BRCU

For detailed installation instructions, please consult the manual : **19440_XXX0_HAND.pdf**

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 **System ceiling**	-
 **Plasterboard**	-
 **Stucanet**	-
 **Wood**	-
 **Concrete**	-
 **Concrete + plaster**	-
 **Lintel + plaster**	-
 **Hollow-core slab**	-
 **Hollow-core slab + plaster**	-
 **Stretched ceiling**	-

FINISH YOUR SPECIFICATION

les batteries de secours



21032 0270 B EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B ☐

Cutout dimension (mm): 27

21032 0270 W EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W ☐

DELTALIGHT

DEEP RINGO HE 93020

19440 9320 BRCU

les alimentations led

of Fixtures

web2print_power_supply_info_box

Min current | Max current



300 90 91 LED POWER SUPPLY 350mA-DC / 15W 2(1)

Dimtype: non dimmable

Cutout dimension (mm): 40



300 90 110 LED POWER SUPPLY 350mA-DC / 10W DIM8 1

Dimtype: fin de phase

Cutout dimension (mm): 42



300 90 116 LED POWER SUPPLY 350mA-DC / 18W DIM8 2->2

Dimtype: fin de phase

Cutout dimension (mm): 55



21012 0515 LED POWER SUPPLY MULTI POWER DIM5 1(1)

Dimtype: DALI

Cutout dimension (mm): 55



21012 0520 LED POWER SUPPLY 350mA-DC / 8W 1(0)

Dimtype: non dimmable

Cutout dimension (mm): 47



21012 0575 LED POWER SUPPLY MULTI POWER DIM5 2->3(2)

Dimtype: DALI

Cutout dimension (mm): 55

Notes: