



OML50 C - LED ARRAY UP HE 1640mm 930 DIM5

31139 9305

 [Bekijk op website](#)



| Algemene info | |
|---------------------------------|--------------------------------------------------------------------------------------------------|
| LOCATIE | binnen |
| STOF EN WATERDICHTHEID | IP20 |
| GEWICHT (KG) | 0.8 |
| INFO | CLUSTER UP: 1932lm/m INCL.DIMMABLE LED POWER SUPPLY (DALI-2 standard) CABLING 1 CIRCUIT |
| Elektrische info | |
| INGANGSSPANNING | 220-240V / 0 50-60Hz |
| KLASSE | I |
| VOEDING | YES |
| DIM TYPE | DALI |
| ENERGIE KLASSE | D |
| CERTIFICATEN | EPD, RCM |
| Info lichtbron | |
| LIGHTSOURCE NAME | LED |
| LICHTBRON | LED cluster 20,4W / CRI>90 (R9: 50) / 3000K / 3168lm |
| TM-30-15 WAARDEN | Rf: 92 / Rg: 100 |
| SDCM | SDCM3 |
| RISK-GROEP | RG1 |
| LM80 | L80 > 60000 |
| LED TECHNIEK (LICHTBRON) | 3168lm // 20,4W // 155lm/W |

Opties

WIRELESS CONTROL DIM5

Notes: