
DELTALIGHT




OVIO 39 ON 93019

REFERENCE 40111 9320 BBR

AVAILABLE IN
BLACK BRONZE 40111 9320 BBR
BRUSHED ANTHRACITE 40111 9320 BRAT
WHITE 40111 9320 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 85° swiveling, 355° rotatable

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1018lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	19°
LED TECHNICS (LIGHT SOURCE)	1018lm //8,6 W // 118lm/W
LED TECHNICS (LUMINAIRE)	706lm // 10W // 71lm/W

Requirements

LED POWER SUPPLY 350/500mA

Accessories

HONEYCOMB 39
SOFTENING LENS 39
SANDBLASTED LENS 39
LINEAR SPREAD LENS 39

For detailed installation instructions, please consult the manual : **40111_XXX0_HAND.pdf**

DELTALIGHT

OVIO 39 ON 93019

40111 9320 BBR


FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 90 63 LED POWER SUPPLY MULTI-POWER DIM9 — 1 -> 4 (4) | 1 -> 4 (4) ☐

Dimtype: 1-10V or DALI or push button


Cutout dimension (mm): 82



300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9 — 2 -> 6 (6) | 1 -> 6 (4) ☐

Dimtype: 1-10V or DALI or push button


Cutout dimension (mm): 84



300 90 124 LED POWER SUPPLY MULTI-POWER DIM7 — 1 -> 2 (2) | 1 -> 2 (1) ☐

Dimtype: 1-10V or push button


Cutout dimension (mm): 55



300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5 — 1 -> 2 (2) | 1 -> 2 (1) ☐

Dimtype: DALI


Cutout dimension (mm): 55



21012 0010 LED POWER SUPPLY MULTI POWER — 1 -> 2 | 1 -> 2 ☐

Dimtype: non-dimmable


Cutout dimension (mm): 50



21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL — 1 -> 3 | 1 -> 3 ☐

Dimtype: WDL = wireless dimmable


Cutout dimension (mm): 54



21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 — 1 -> 2 | 1 -> 2 ☐

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 48



21012 0408 LED POWER SUPPLY 120V - 500mA-DC / 24W DIM8 — - | 2 -> 2 (2) ☐


Dimtype: mains (phase cut-off)

Cutout dimension (mm): 55

DELTALIGHT

OVIO 39 ON 93019


40111 9320 BBR



21012 0515 LED POWER SUPPLY MULTI POWER DIM5 — 1 -> 1 (1) | 1 -> 1 (1)

Dimtype: DALI

Cutout dimension (mm): 55



21012 0595 LED POWER SUPPLY 500mA-DC 10W DIM5 — - | 1 -> 1

Dimtype: DALI

Cutout dimension (mm): 35

Light altering devices

32210 0210 SOFTENING LENS 39

32210 0220 SANDBLASTED LENS 39

32210 0230 LINEAR SPREAD LENS 39



32210 0240 HONEYCOMB 39

Notes: