


COMPO S WALLWASH HP TW 940

9 15726 9000 C

AVAILABLE IN
CHROMED 9 15726 9000 C
WHITE 9 15726 9000 W



 [View on website](#)



EXCLUSIVELY AVAILABLE IN INDIA

General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 120
RECESSED DEPTH (MM)	114
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.18
ADJUSTABILITY	0° to 30° swiveling, 355° rotatable
Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	F
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 7W / CRI>90 / 1800K-4000K / 605lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 56000
BEAMANGLE	NA
LED TECHNICS (LIGHT SOURCE)	605lm // 7W // 89lm/W
LED TECHNICS (LUMINAIRE)	229lm // 8W // 28lm/W
Requirements	
LED POWER SUPPLY 200 mA - DC	

For detailed installation instructions, please consult the manual : [9_15726_XXX0_HAND.pdf](#)

COMPO S WALLWASH HP TW 940

9 15726 9000 C

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
	 15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	 15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required
	 15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	 15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required
	 15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	 15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required

FINISH YOUR SPECIFICATION

LED Power supply	# of Fixtures
 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.	Min current Max current

15710 5800 LED POWER SUPPLY MULTIPOWER 12W DALI DT8 200mA

1

Mounting kits	
 15710 0010 B MOUNTING KIT COMPO S TRIM B	☐
Cutout dimension (mm): 55	
 15710 0010 W MOUNTING KIT COMPO S TRIM W	☐
 15710 0040 MOUNTING KIT COMPO S TRIMLESS	☐
Cutout dimension (mm): 55	

Notes: