


COMPO S WALLWASH HP TW 940

9 15726 9000 C


AVAILABLE IN

CHROMO 9 15726 9000 C

BLANCO 9 15726 9000 W



EXCLUSIVELY AVAILABLE IN INDIA



[View on website](#)



General info

LOCATION	interior
INSTALLATION	Techo Empotrado
CUTOUT SHAPE/SIZE (MM)	redondo - 120
RECESSED DEPTH (MM)	114
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.18
ADJUSTABILITY	0° to 30° giratorio, 355° orientable

Electrical info

CLASS	III
DIM TYPE	dependiendo del tipo de fuente de alimentación externa
ENERGY CLASS	F

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 7W / CRI>90 / 1800K-4000K / 605lm
RVALUES	rf: 89 / Rg: 100
SDMC	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 56000
BEAMANGLE	NA
LED TECHNICS (LIGHT SOURCE)	605lm // 7W // 89lm/W
LED TECHNICS (LUMINAIRE)	229lm // 8W // 28lm/W

Requirements

LED POWER SUPPLY 200 mA - DC

For detailed installation instructions, please consult the manual : [9_15726_XXX0_HAND.pdf](#)

COMPO S WALLWASH HP TW 940

9 15726 9000 C

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
	 15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	 15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required
	 15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	 15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required
	 15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	 15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required

FINISH YOUR SPECIFICATION

Fuente de alimentación LED

of Fixtures

 web2print_power_supply_info_box	Min current Max current
15710 5800 LED POWER SUPPLY MULTIPOWER 12W DALI DT8 200mA	1

Mounting Kit

	15710 0010 B MOUNTING KIT COMPO S TRIM B	☐
Cutout dimension (mm): 55		
	15710 0010 W MOUNTING KIT COMPO S TRIM W	☐
	15710 0040 MOUNTING KIT COMPO S TRIMLESS	☐
Cutout dimension (mm): 55		

Notes: