



## ENTERO RD-M TRIMLESS TW 94030



28467 9020 GC

AVAILABLE IN

**BLACK** 28467 9020 B

**FULL WHITE** 28467 9020 FW

**GOLD COLOURED** 28467 9020 GC



[View on website](#)



### General info

|                               |                                                                                                               |
|-------------------------------|---------------------------------------------------------------------------------------------------------------|
| <b>LOCATION</b>               | indoor                                                                                                        |
| <b>INSTALLATION</b>           | Ceiling Recessed                                                                                              |
| <b>CUTOUT SHAPE/SIZE (MM)</b> | round - Ø KIT                                                                                                 |
| <b>RECESSED DEPTH (MM)</b>    | 135                                                                                                           |
| <b>INGRESS PROTECTION</b>     | IP20                                                                                                          |
| <b>WEIGHT (KG)</b>            | 0.4                                                                                                           |
| <b>ADJUSTABILITY</b>          | 0° to 30° swiveling, 355° rotatable                                                                           |
| <b>INFORMATION</b>            | REFLECTOR FL-30°<br>EXCL.LED POWER SUPPLY 500mA-DC TW - (DALI DT8)<br>Optional REFLECTORS 18° & 45° available |

### Electrical info

|                     |                           |
|---------------------|---------------------------|
| <b>CLASS</b>        | III                       |
| <b>DIM TYPE</b>     | depending on power supply |
| <b>ENERGY CLASS</b> | E                         |
| <b>CERTIFICATES</b> | CB, ENEC, EPD             |

### Lightsource info

|                                    |                                                      |
|------------------------------------|------------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                                  |
| <b>LIGHTSOURCE</b>                 | LED array 9W / CRI>90 (R9: 50) / 1800K-4000K / 979lm |
| <b>TM-30 VALUES</b>                | rf: 89 / Rg: 100                                     |
| <b>SDCM</b>                        | SDCM2                                                |
| <b>RISKGROUP</b>                   | RG1                                                  |
| <b>LM80</b>                        | L90B10 > 50000                                       |
| <b>BEAMANGLE</b>                   | 30°                                                  |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 979lm // 9W // 109lm/W                               |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 709lm // 10,4W // 68lm/W                             |

### Requirements

MOUNTING KIT ENTERO ROUND M

LED POWER SUPPLY 500mA-DC TW (Remote)

### Accessories

ENTERO M HONEYCOMB

ENTERO M LINEAR SPREAD LENS

ENTERO M SPREAD LENS

ENTERO M SOFTENING LENS

ENTERO M GLASS SBL

## ENTERO RD-M TRIMLESS TW 94030

28467 9020 GC

For detailed installation instructions, please consult the manual : [28467\\_XXX0\\_HAND.pdf](#)

### CEILING COMPATIBILITY

| Ceiling Type                                                                                                         | Mounting Kit                                                                                                                     |          |
|----------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|----------|
|  <b>System ceiling</b>               |  28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.   | Required |
|  <b>Plasterboard</b>                 |  28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.   | Required |
|  <b>Stucanet</b>                     |  28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.   | Required |
|  <b>Concrete + plaster</b>           |  28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.   | Required |
|  <b>Lintel + plaster</b>            |  28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A. | Required |
|  <b>Hollow-core slab + plaster</b> |  28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A. | Required |
|  <b>Stretched ceiling</b>          |  28400 0080 - MOUNTING KIT ENTERO RD-M CSC    | Required |
|                                                                                                                      |  28400 0140 - MOUNTING KIT ENTERO RD-M WSC    | Required |

### FINISH YOUR SPECIFICATION


#### LED power supplies

#### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



**21012 0355** LED POWER SUPPLY 500mA-DC 2CH TW DIM5

Dimtype: DALI

Cutout dimension (mm): 85


2

# DELTALIGHT

## ENTERO RD-M TRIMLESS TW 94030

28467 9020 CC

### Mounting kits




**28400 0020** MOUNTING KIT ENTERO RD-M O.F.A.

☐

Cutout dimension (mm): 127

### Mounting kits stretched ceiling



**28400 0080** MOUNTING KIT ENTERO RD-M CSC

☐


**28400 0140** MOUNTING KIT ENTERO RD-M WSC

☐

### Light altering devices




**28500 0070** ENTERO M LINEAR SPREAD LENS

☐


**28500 0080** ENTERO M SPREAD LENS

☐

**28500 0090** ENTERO M SOFTENING LENS

☐

**28500 0100** ENTERO M GLASS SBL

☐


**28500 0110 B** ENTERO M HONEYCOMB SINGLE USE B

☐

# DELTALIGHT

## ENTERO RD-M TRIMLESS TW 94030

28467 9020 GC



**28500 0120 B** ENTERO M HONEYCOMB DOUBLE USE B

☐

### Replaceable reflector / lens



**24611 0220** SPY 66 REFLECTOR 18°

☐



**24611 0230** SPY 66 REFLECTOR 30°

☐



**24611 0240** SPY 66 REFLECTOR 45°

☐

Notes: