





SOLI - 66 92730 DIM5

27123 9225 W

AVAILABLE IN
BLACK 27123 9225 B
WHITE 27123 9225 W



 [View on website](#)



General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	0° to 90° swiveling, 360° rotatable
INFORMATION	REFLECTOR FL-30° EXCL.LED POWER SUPPLY 48V-DC Optional REFLECTORS 18° & 45° available

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, LCA

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 21W / CRI>90 (R9: 60) / 2700K / 2356lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	30°
LED TECHNICS (LIGHT SOURCE)	2356lm // 21W // 112lm/W
LED TECHNICS (LUMINAIRE)	1624lm // 24,2W // 67lm/W

Requirements

SPY 66 TUBE
LED POWER SUPPLY 48V-DC

Accessories

HONEYCOMB 57
SPREAD LENS 57
LINEAR SPREAD LENS 57
SOFTENING LENS 57
GLASS SBL 57






DELTALIGHT

SOLI - 66 92730 DIM5

27123 9225 W

For detailed installation instructions, please consult the manual : [27123_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION

LED power supplies		# of Fixtures
 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
 300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN Dimtype: non-dimmable		4 ☐
 300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN Dimtype: non-dimmable		10 ☐
 21012 0230 LED POWER SUPPLY 48V-DC / 100W Dimtype: non-dimmable Cutout dimension (mm): 40		4 ☐
 21012 0240 LED POWER SUPPLY 48V-DC / 200W Dimtype: non-dimmable Cutout dimension (mm): 40		8 ☐
Light altering devices		
 24611 0150 B HONEYCOMB 57 SINGLE USE B		☐
 24611 0160 GLASS SBL 57		☐

DELTALIGHT

SOLI - 66 92730 DIM5

27123 9225 W



24611 0170 LINEAR SPREAD LENS 57

☐

24611 0190 SOFTENING LENS 57

☐

24611 0200 SPREAD LENS 57

☐

24611 0210 B HONEYCOMB 57 DOUBLE USE B

☐

Finish your product



24611 0100 B SPY 66 TUBE B

☐

24611 0100 FBR SPY 66 TUBE FBR

☐

24611 0100 FG SPY 66 TUBE FG

☐

24611 0100 GC SPY 66 TUBE GC

☐

24611 0100 W SPY 66 TUBE W

☐

Replaceable reflector / lens



24611 0220 SPY 66 REFLECTOR 18°

☐

DELTALIGHT

SOLI - 66 92730 DIM5

27123 9225 W



24611 0230 SPY 66 REFLECTOR 30°




24611 0240 SPY 66 REFLECTOR 45°




COMPATIBLE COMPOSABLES

SOLISCAPE profile

Available Colours



27111 0020 SOLI - PROFILE 2m



27111 0030 SOLI - PROFILE 3m



Notes: