DELTALIGHT



D-LINER 30 INF LOC2 1390 94058 RD

REFERENCE 32086 9420 B-B

AVAILABLE IN
BLACK-BLACK 32086 9420 B-B
WHITE-WHITE 32086 9420 W-W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
INGRESS PROTECTION	IP20
WEIGHT (KG)	0
ADJUSTABILITY	non adjustable
INFORMATION	60 x REFLECTOR FL-58° EXCL.LED POWER SUPPLY 650mA-DC INCL.1 x CABLE 2 x 0,75mm² - 0,5m + WIELAND PLUG GST08i2 male green

Electrical info	
CLASS	III
ENERGY CLASS	C
CERTIFICATES	EPD

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 21,6W / CRI>90 / 4000K / 3942lm
LED TECHNICS (LIGHT SOURCE)	3942lm // 21,6W // 183lm/W
LED TECHNICS (LUMINAIRE)	3118lm // 25W // 126lm/W

Requirements

LED POWER SUPPLY SET LOC PARALLEL

Options

CONNECTING CABLE LOC PARALLEL

For detailed installation instructions, please consult the manual : **32086_XXX0_HAND.pdf**

DELTALIGHT

D-LINER 30 INF LOC2 1390 94058 RD

32086 9420 B-B

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 **Acoustic climate-control ceiling Hunter Douglas 30BD**	-

FINISH YOUR SPECIFICATION

Emergency units

of Fixtures

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



32010 0195 EMERGENCY UNIT 1h LOC PARALLEL DIM5 — 1

Dimtype: DALI

Current supply



32010 1200 T CONNECTOR LOC PARALLEL



32010 1310 CONNECTING CABLE LOC PARALLEL 1m



32010 1320 CONNECTING CABLE LOC PARALLEL 2m



32010 1330 CONNECTING CABLE LOC PARALLEL 3m



32010 1340 CONNECTING CABLE LOC PARALLEL 4m

DELTALIGHT

D-LINER 30 INF LOC2 1390 94058 RD

32086 9420 B-B



32010 1350 CONNECTING CABLE LOC PARALLEL 5m

LED power supplies

of Fixtures

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



32010 0115 LED POWER SUPPLY SET LOC PARALLEL 650mA / 35W DIM5 — 1

Dimtype: DALI



32010 0165 LED POWER SUPPLY SET LOC PARALLEL 1300mA /100W DIM5 — 2->2

Dimtype: DALI



32010 0445 LED POWER SUPPLY SET LOC PARALLEL 1950mA / 100W DIM5 — 3->3

Dimtype: DALI

Notes: