




SPYCO 70 94024 ADM

19920 9420 B

AVAILABLE IN
BLACK 19920 9420 B
FULL WHITE 19920 9420 FW



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Mains voltage track Mains voltage track mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.6
ADJUSTABILITY	0° to 90° swiveling, 350° rotatable
INFORMATION	INCL.LED POWER SUPPLY 450/500mA-DC Max. 450mA with HONEYCOMB
Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	E
CERTIFICATES	EPD, RCM
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	@ 500mA: LED array 17,2W / CRI>90 (R9: 79) / 4000K / 2222lm Or @ 450mA (+HONEYCOMB): LED array 15,3W / CRI>90 (R9: 79) / 4000K / 2024lm
TM-30 VALUES	@ 500mA: Rf: 90 / Rg: 99 @ 450mA (+HONEYCOMB): Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	24°
LED TECHNICS (LIGHT SOURCE)	@ 500mA: 2222lm // 17,2W // 130lm/W Or @ 450mA (+HONEYCOMB): 2024lm // 15,3W // 132lm/W
LED TECHNICS (LUMINAIRE)	@ 500mA: 1849lm // 19,8W // 93lm/W Or @ 450mA (+HONEYCOMB): 1192lm // 17,6W // 68lm/W
Requirements	
TRACK 3F ON	
Accessories	
SPYCO 70 HONEYCOMB	

For detailed installation instructions, please consult the manual : [19920_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Light altering devices



19922 0010 B SPYCO 70 HONEYCOMB B



COMPATIBLE TRACKS

TRACK 3F ON			Available Colours
28900 0020	TRACK 3F ON 2m	2000 m 1.8 kg	
28900 0030	TRACK 3F ON 3m	3000 m 2.7 kg	

Notes: