



M26L - SPY 39 FOCUS 927 DIM5

23430 9205 GC

AVAILABLE IN

BLACK 23430 9205 B

BRUSHED ALU 23430 9205 BRA

BRUSHED ANTHRACITE 23430 9205 BRAT

BRUSHED COPPER 23430 9205 BRCU

BRUSHED GOLD 23430 9205 BRG


BRUSHED OLD BRONZE 23430 9205 BROB

FLEMISH BRONZE 23430 9205 FBR


FLEMISH GOLD 23430 9205 FG

GOLD COLOURED 23430 9205 GC

WHITE 23430 9205 W



0-85°/355°



 [View on website](#)



General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 85° swiveling, 360° rotatable
INFORMATION	ADJUSTABLE BEAM 15°-45° EXCL.LED POWER SUPPLY 48V-DC

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	F

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 60) / 2700K / 974lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUPE	RG1
LM80	L90B10 > 50000
BEAMANGLE	15°-45°
LED TECHNICS (LIGHT SOURCE)	974lm // 8,6W // 113lm/W
LED TECHNICS (LUMINAIRE)	290lm // 9,9W // 29lm/W

Requirements

LED POWER SUPPLY 48V-DC

For detailed installation instructions, please consult the manual : [23430_XXX5_HAND.pdf](#)

DELTALIGHT

M26L - SPY 39 FOCUS 927 DIM5

23430 9205 GC

FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

10


Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

24

Dimtype: non-dimmable



21012 0230 LED POWER SUPPLY 48V-DC / 100W

10

Dimtype: non-dimmable

Cutout dimension (mm): 40



21012 0240 LED POWER SUPPLY 48V-DC / 200W

20

Dimtype: non-dimmable

Cutout dimension (mm): 40

COMPATIBLE COMPOSABLES

SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)

Available Colours



23358 0000 SLM26L - PROFILE



23358 0010 SLM26L - PROFILE 1m



23358 0020 SLM26L - PROFILE 2m



DELTALIGHT

M26L - SPY 39 FOCUS 927 DIM5

23430 9205 GC



23358 0030 SLM26L - PROFILE 3m



Notes: