

M-GIBBO



A fresh touch in the Delta Light range is the use of handblown glass globes, a decorative eye-catcher that combines warm tints and materials with the latest LED technology. The Gibbo is a suspended fixture with a base positioned at an angle so that the globe appears to be rolling away. The glass is handblown and is available in transparent, opal or amber tinted versions. The golden brown colour gives the Gibbo a warm presence, which is attractive in compositions above tables and in interiors with warm accents and materials. The base for the Gibbo is available in black or white.

| Specification | |
|----------------|-------|
| Adjustability: | Fixed |
| Rating: | IP20 |

| Performance | |
|------------------|-------------|
| LED Maintenance: | L90>50,000h |
| McAdam Step: | 2 |
| CRI: | 90 |
| *SP: | 7W |

| Delivered Lumens | 2700K | 3000K | 3500K |
|------------------|-------|-------|-------|
| M-Gibbo: | 738lm | 771lm | 800lm |

Listing

ETL certified to US and Canadian safety standards.

Warranty

5-year limited warranty.

Ordering

ALL BOXES MUST BE FILLED IN TO CORRECTLY ORDER

Example: GBOPC-SP27-B-A-M-MDL

| Luminaire | Style | Power* | CCT | Finish | Glass Bowl | Application ⁽¹⁾ | Controls |
|---------------------|--|-----------------------------|--|--|--|---|---|
| GBO GIBBO | PC Pendant, cable suspended | SP Standard Power | 27 2700K 30 3000K 35 3500K | B Black W White | A Amber C Clear O Opal | M Shiftline M26H / Shiftline M26H + SBL ⁽²⁾ / Shiftline M26L Splitline M20 / Splitline M20 ST / Splitline M52 Profile | MDL ⁽²⁾ 0-10V dim via Modulator D5 Dali dim WD ⁽²⁾ Wireless dim |

¹ Profile system hardware specified separately.
² Shiftline M26H + SBL only available with Controls D5.

Related Products

M-Microspy C, M-Tweeter BL, Gibbo

Finish Options

M-GIBBO




GLASS BOWL



Photometric Data

GIBBO



Installation Options

Delta Light's Magnetic Systems all utilize 48V remote power supplies. With a maximum of 96W per power supply, the below details maximum magnetic modules per power feed.

| Maximum Capacity per Remote Power Supply | M-Gibbo |
|--|---------|
| *SP: | 11 |

FOR SYSTEM HARDWARE, REFER TO THE FOLLOWING PROFILE SYSTEMS:
Shiftline M26H (surface/suspended, high-height, optional curved corner connectors)
Shiftline M26H + SBL (surface/suspended, high-height, integral continuous light line)
Shiftline M26L (surface/suspended, low-height, stacking possible)
Splitline M20 (recessed, knife-edge, optional curved corner connectors)
Splitline M20 ST (recessed, small trim)
Splitline M52 (recessed, knife-edge)

As technology changes, please use information above as guidance. For most recent updated information please contact factory. Specifications subject to change without notice.