





KIX II PIN 93030

13537 9320 N

AVAILABLE IN
ALU GREY 13537 9320 A
ANTHRACITE 13537 9320 N
PINE GREEN 13537 9320 PGR



 [View on website](#)



General info	
LOCATION	outdoor
INSTALLATION	Floor Surface mounted
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK03
WEIGHT (KG)	1.2
ADJUSTABILITY	180° swiveling, 360° rotatable
INFORMATION	REFLECTOR FL-30° INCL.1 x CABLE H05 RN-F 2 x 1mm ² 2m INCL.LED POWER SUPPLY 350mA-DC

Electrical info	
ELECTRICAL	100-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	C

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	30°
LED TECHNICS (LIGHT SOURCE)	787lm // 5,8W // 135lm/W
LED TECHNICS (LUMINAIRE)	644lm // 6,7W // 96lm/W

Options	
CBOX	
IP68 CONNECTION KIT	
IP68 CONNECTOR 3P	

Accessories	
KAP KIX	
HONEYCOMB KIX	

For detailed installation instructions, please consult the manual : [13537_XXX0_HAND.pdf](#)


FINISH YOUR SPECIFICATION

Waterproof connection parts



216 12 00 CBOX

Cutout dimension (mm): 142 x 142

☐

216 12 01 IP68 CONNECTION KIT

☐

216 12 02 IP68 CONNECTOR 3P

☐

Light altering devices



232 10 00 N KAP KIX N

☐

232 10 03 N HONEYCOMB KIX N

☐

Notes: