

LOGIC WW



An in-grade luminaire with nearly 800 delivered lumens, LOGIC can be used to accentuate trees or sculptures, but also to uplight facades or large garden features, to create a sense of depth or indicate the right direction along paths and driveways. Offered with or without a trim flange, LOGIC 60 R can be powered via 24V, if dimming is not important, or via 350mA for full-range dimming. LOGIC 60 R also has some unique light effect options with the SP version that creates a 6 degree stripe of light, or the MOON version that reduces glare when mounted adjacent to an occupied space or walkway.

Specification	Logic 60 R WW	Logic 90 R WW
Floor Cut-out:	2 ³ / ₈ "	3 ¹¹ / ₁₆ "
Adjustability:	Fixed	
Rating:	IP67	

Performance	Logic 60 R WW	Logic 90 R WW
CRI:	90	
*SP:	5W	7W

Delivered Lumens	3000K	3500K
Logic 60 R WW:	159Lm	
Logic 60 R WW SBL:	155Lm	
Logic 90 R WW:	488Lm	506Lm
Logic 90 R WW SBL:	401Lm	415Lm
Logic 90 RA WW:	488Lm	506Lm
Logic 90 RA WW SBL:	401Lm	415Lm

Listing

ETL certified to US and Canadian safety standards.

Warranty

5-year limited warranty.

Ordering

ALL BOXES MUST BE FILLED IN TO CORRECTLY ORDER

Example: LGC60R-ANO-30ND-24-SPWWFX-GBRMT

Luminaire	Size	Shape	Finish	CCT	Controls***	Power*	Optic	Function	Installation	Application
LGC LOGIC	60 60mm / 2 ³ / ₈ "	R Round without Flange	ANO Anodized Aluminum	30 3000K	ND-24 Non-Dim 24V	SP Standard Power	WW Wallwash	FX Floor, Exterior Use	GB Inground Box	RMT Remote Power Supply
	90 90mm / 3 ⁹ / ₁₆ "	R Round without Flange	ANO Anodized Aluminum	30 3000K	ND-24 Non-Dim 24V					
		RA Round with Flange	B ⁽¹⁾ Black Aluminum	35 3500K	D1-UNV 0-10V dim 120-277V D8-120 FE ELV dim 120V		WS Wallwash with SBL Lens			

¹ Only available with Shape RA.

*** Contact factory for Dali, DMX, or other dimming options.

Related Products

Logic 60, Logic 90, Logic 40

Finish Options

LOGIC 60 R



LOGIC 90 R




LOGIC 90 RA



Accessories





JUNCTION BOX
6 216 12 00





IP68 CONNECTOR 3P
6 216 12 03

Photometric Data

LOGIC 60



LOGIC 90






Installation Options

REMOTE DRIVER

REMOTE DRIVER (With Controls ND-120)


A: 8" x B: 2"-1/2 x C: 2"-1/2
A: 203mm x B: 64mm x C: 64mm

- For Remote application
- ETL Listed
- Damp rated



A: 12" x B: 2"-7/8 x C: 4"-1/4
A: 305mm x B: 72mm x C: 108mm

- For Remote application
- ETL Listed
- Damp rated



GB - LOGIC 60 BOX R

GB - GENIE BOX 90 R



Used with LOGIC 60



Used with LOGIC 90

Driver Options

D1		Dimmer Compatibility	
• Dimming Control	0-10V	• Leviton IP710-DLZ	
• Dimming Range	1-100%	• Lutron DDTV-XX	
• Dim to off	yes at 0.7mA	• WattStopper ADF-120277	
• Power Factor @ Full Load	>0.9	• Synergy Lighting Controls ISD BC	
• Efficiency @ Full Load	≥87		
• THD @ Full Load	<20%		
• Title 24 Compliant			
D8		Dimmer Compatibility	
• Dimming Control	Phase Control	• Leviton IPE04-1LZ	
• Dimming Range	10-100%	• Lutron DVELV-300P	
• Dim to off	no		
• Power Factor @ Full Load	>0.9		
• Efficiency @ Full Load	≥78		
• THD @ Full Load	<12%		
ND			
• Dimming Control	NON DIMMABLE		
• Power Factor @ Full Load	>0.95		
• Efficiency @ Full Load	≥90		
• THD @ Full Load	<10%		

As technology changes, please use information above as guidance. For most recent updated information please contact factory. Specifications subject to change without notice.