



## M26L - BOXY L 92733 DIM5

10736 9225 B-B



AVAILABLE IN

**BLACK-BLACK** 10736 9225 B-B

**BLACK-FLEMISH BRONZE** 10736 9225 B-FBR

**BLACK-FLEMISH GOLD** 10736 9225 B-FG

**WHITE-WHITE** 10736 9225 W-W



[View on website](#)



### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Low voltage systems Low voltage system mounted
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	0.4
<b>ADJUSTABILITY</b>	non adjustable
<b>INFORMATION</b>	REFLECTOR FL-33° EXCL.LED POWER SUPPLY 48V-DC

### Electrical info

<b>ELECTRICAL</b>	48V-DC
<b>CLASS</b>	III
<b>DIM TYPE</b>	DALI
<b>ENERGY CLASS</b>	E
<b>CERTIFICATES</b>	CB, ENEC

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED array 8,6W / CRI>90 (R9: 60) / 2700K / 1041lm
<b>TM-30 VALUES</b>	rf: 89 / Rg: 100
<b>SDCM</b>	SDCM1
<b>RISKGROUP</b>	RG1
<b>LM80</b>	L90B10 > 50000
<b>BEAMANGLE</b>	33°
<b>LED TECHNICS (LIGHT SOURCE)</b>	1041lm // 8,6W // 121lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	697lm // 9,9W // 70lm/W

### Remarks

Take a look at our **MAGNETIC PROFILES** movie

### Requirements

LED POWER SUPPLY 48V-DC

### Accessories

BOXY HONEYCOMB  
BOXY SOFTENING LENS  
BOXY GLASS SBL

# DELTALIGHT

## M26L - BOXY L 92733 DIM5


10736 9225 B-B

For detailed installation instructions, please consult the manual : [10736\\_XXX5\\_HAND.pdf](#)


### FINISH YOUR SPECIFICATION

#### LED power supplies

#### # of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN

10


Dimtype: non-dimmable



**300 89 48 240** LED POWER SUPPLY 48V-DC / 240W DIN

24

Dimtype: non-dimmable




**21012 0230** LED POWER SUPPLY 48V-DC / 100W

10

Dimtype: non-dimmable

Cutout dimension (mm): 40



**21012 0240** LED POWER SUPPLY 48V-DC / 200W

20

Dimtype: non-dimmable

Cutout dimension (mm): 40

#### Light altering devices



**251 70 03 01 B** BOXY HONEYCOMB B



**251 70 03 01 W** BOXY HONEYCOMB W



**251 70 03 04 B** BOXY SOFTENING LENS B



# DELTALIGHT

## M26L - BOXY L 92733 DIM5

10736 9225 B-B

**251 70 03 04 W** BOXY SOFTENING LENS W



**251 70 03 05 B** BOXY GLASS SBL B




**251 70 03 05 W** BOXY GLASS SBL W




### COMPATIBLE COMPOSABLES

#### SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)


#### Available Colours




**23358 0000** SLM26L - PROFILE



**23358 0010** SLM26L - PROFILE 1m



**23358 0020** SLM26L - PROFILE 2m



**23358 0030** SLM26L - PROFILE 3m



Notes: