
DELTALIGHT




COMPO S WALLWASH HP SOFT 930

REFERENCE 9 15724 9000 C

AVAILABLE IN
CHROMED 9 15724 9000 C
WHITE 9 15724 9000 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 120
RECESSED DEPTH (MM)	114
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.164
ADJUSTABILITY	0° to 30° swiveling, 355° rotatable

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	F

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,7W / CRI>90 (R9: 50) / 3000K-1800K / 734lm
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	NA
LED TECHNICS (LIGHT SOURCE)	734lm // 8,7W // 99lm/W
LED TECHNICS (LUMINAIRE)	278lm // 10W // 28lm/W

Requirements

LED POWER SUPPLY 350 mA - DC

For detailed installation instructions, please consult the manual : **9_15724_XXX0_HAND.pdf**

DELTALIGHT

COMPO S WALLWASH HP SOFT 930

9 15724 9000 C

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 **System ceiling**	15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required
 **Plasterboard**	15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required
 **Wood**	15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required

FINISH YOUR SPECIFICATION

LED Power supply

of Fixtures

Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

15710 3800	LED POWER SUPPLY MULTIPOWER 10W DIM8 350mA	1 ☐
15710 4500	LED POWER SUPPLY MULTIPOWER 12W DIM1 350mA	1 ☐
15710 5100	LED POWER SUPPLY MULTIPOWER 8W DALI DT6 350mA	1 ☐

Dimtype: DALI

Mounting kits



15710 0010 B MOUNTING KIT COMPO S TRIM B ☐

Cutout dimension (mm): 55

15710 0010 W MOUNTING KIT COMPO S TRIM W ☐



15710 0040 MOUNTING KIT COMPO S TRIMLESS ☐

Cutout dimension (mm): 55

DELTALIGHT

COMPO S WALLWASH HP SOFT 930

9 15724 9000 C

Notes: