



OVIO 39 ON 93019

REFERENCE



40111 9320 BRAT

AVAILABLE IN

BLACK BRONZE 40111 9320 BBR

BRUSHED ANTHRACITE 40111 9320 BRAT

WHITE 40111 9320 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 85° swiveling, 355° rotatable

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1018lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	19°
LED TECHNICS (LIGHT SOURCE)	1018lm // 8,6 W // 118lm/W
LED TECHNICS (LUMINAIRE)	706lm // 9,9W // 71lm/W

Requirements

LED POWER SUPPLY 350/500mA

Accessories

HONEYCOMB 39

SOFTENING LENS 39

SANDBLASTED LENS 39

LINEAR SPREAD LENS 39

For detailed installation instructions, please consult the manual : [40111_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION


LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




300 90 63 LED POWER SUPPLY MULTI-POWER DIM9

1 -> 4 (4) | 1 -> 4 (4)

☐

Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 82




300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9

2 -> 6 (6) | 1 -> 6 (4)

☐

Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 84




300 90 124 LED POWER SUPPLY MULTI-POWER DIM7

1 -> 2 (2) | 1 -> 2 (1)

☐

Dimtype: 1-10V or push button

Cutout dimension (mm): 55




21012 0010 LED POWER SUPPLY MULTI POWER

1 -> 2 | 1 -> 2

☐

Dimtype: non-dimmable

Cutout dimension (mm): 50




21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL

1 -> 3 | 1 -> 3

☐

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 54




21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8

1 -> 2 | 1 -> 2

☐

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 48




21012 0408 LED POWER SUPPLY 120V - 500mA-DC / 24W DIM8

- | 2 -> 2 (2)

☐

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 55



21012 0515 LED POWER SUPPLY MULTI POWER DIM5

1 -> 1 (1) | 1 -> 1 (1)

☐

Dimtype: DALI

Cutout dimension (mm): 55

DELTALIGHT

OVIO 39 ON 93019

40111 9320 BRAT



21012 0595 LED POWER SUPPLY 500mA-DC 10W DIM5

- | 1 -> 1

☐

Dimtype: DALI

Cutout dimension (mm): 35

Light altering devices



32210 0210 SOFTENING LENS 39

☐

32210 0220 SANDBLASTED LENS 39

☐

32210 0230 LINEAR SPREAD LENS 39

☐

32210 0240 HONEYCOMB 39

☐

Notes: