





INFORM 40 SQ 320 DOWN TW 1 DT8 85063 DIM5

30715 8035 W-B

AVAILABLE IN

BLACK-BLACK 30715 8035 B-B

WHITE-BLACK 30715 8035 W-B



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted,Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	5
ADJUSTABILITY	non adjustable
INFORMATION	INCL.DIMMABLE LED POWER SUPPLY (DALI DT8) EXCL.CABLE SUSPENSION MELANOPIC LIGHT TECHNOLOGY

Electrical info

ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	E

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	@ 2700K: LED cluster 29,8W / CRI>80 (R9: 50) / 2700K-5000K / 3904lm Or @ 5000K: LED cluster 27W / CRI>80 (R9: 50) / 2700K-5000K / 4672lm
SDCM	SDCM3
RISKGROUP	RG1
BEAMANGLE	63°
LED TECHNICS (LIGHT SOURCE)	@ 2700K: 3904lm // 29,8W // 131lm/W Or @ 5000K: 4672lm // 27W // 173lm/W
LED TECHNICS (LUMINAIRE)	@ 2700K: 2701lm // 34,3W // 79lm/W Or @ 5000K: 3233lm // 31W // 104lm/W


Options

INF40 SQ 320/360 - SUSPENSION SET
CABLE BASE R / S

For detailed installation instructions, please consult the manual : [30715_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Current supply

	41 203 99 55 ANO CABLE BASE R ANO	☐
	203 99 55 B CABLE BASE R B	☐
	203 99 55 W CABLE BASE R W	☐
	41 203 99 56 ANO CABLE BASE S ANO	☐
	203 99 56 B CABLE BASE S B	☐
	203 99 56 W CABLE BASE S W	☐

Fixation components

	30710 0020 B INF40 SQ 320/360 - SUSPENSION SET 1,6m B	☐
	30710 0020 W INF40 SQ 320/360 - SUSPENSION SET 1,6m W	☐
	30710 0040 B INF40 SQ 320/360 - SUSPENSION SET 3,0m B	☐
	30710 0040 W INF40 SQ 320/360 - SUSPENSION SET 3,0m W	☐

DELTALIGHT

INFORM 40 SQ 320 DOWN TW 1 DT8 85063 DIM5

30715 8035 W-B

Notes: