DELTALIGHT

# OVIO 39 ON 93019

**REFERENCE** 40111 9320 W

AVAILABLE IN
**BLACK BRONZE** 40111 9320 BBR
**BRUSHED ANTHRACITE** 40111 9320 BRAT
**WHITE** 40111 9320 W







View on website

| General info | |
|---|---|
| **LOCATION** | indoor |
| **INSTALLATION** | Ceiling Surface mounted |
| **INGRESS PROTECTION** | IP20 |
| **WEIGHT (KG)** | 0.3 |
| **ADJUSTABILITY** | 0° to 85° swiveling, 355° rotatable |

| Electrical info | |
|---|---|
| **CLASS** | III |
| **DIM TYPE** | depending on power supply |
| **ENERGY CLASS** | E |

| Lightsource info | |
|---|---|
| **LIGHTSOURCE NAME** | LED |
| **LIGHTSOURCE** | LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1018lm |
| **TM-30 VALUES** | Rf: 90 / Rg: 99 |
| **SDCM** | SDCM1 |
| **RISKGROUP** | RG1 |
| **LM80** | L90B10 > 50000 |
| **BEAMANGLE** | 19° |
| **LED TECHNICS (LIGHT SOURCE)** | 1018lm //8,6 W // 118lm/W |
| **LED TECHNICS (LUMINAIRE)** | 706lm // 10W // 71lm/W |

**Requirements**

LED POWER SUPPLY 350/500mA

**Accessories**

HONEYCOMB 39
SOFTENING LENS 39
SANDBLASTED LENS 39
LINEAR SPREAD LENS 39

For detailed installation instructions, please consult the manual : **40111_XXX0_HAND.pdf**

DELTALIGHT

# OVIO 39 ON 93019

40111 9320 W

## FINISH YOUR SPECIFICATION

### LED power supplies

### # of Fixtures

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

**Min current | Max current**




**300 90 63** LED POWER SUPPLY MULTI-POWER DIM9 — 1 -> 4 (4) | 1 -> 4 (4) ☐

**Dimtype: 1-10V or DALI or push button**

**Cutout dimension (mm): 82**




**300 90 69** LED POWER SUPPLY MULTI-POWER HV DIM9 — 2 -> 6 (6) | 1 -> 6 (4) ☐

**Dimtype: 1-10V or DALI or push button**

**Cutout dimension (mm): 84**




**300 90 124** LED POWER SUPPLY MULTI-POWER DIM7 — 1 -> 2 (2) | 1 -> 2 (1) ☐

**Dimtype: 1-10V or push button**

**Cutout dimension (mm): 55**




**300 90 125** LED POWER SUPPLY MULTI-POWER MINI DIM5 — 1 -> 2 (2) | 1 -> 2 (1) ☐

**Dimtype: DALI**

**Cutout dimension (mm): 55**




**21012 0010** LED POWER SUPPLY MULTI POWER — 1 -> 2 | 1 -> 2 ☐

**Dimtype: non-dimmable**

**Cutout dimension (mm): 50**




**21012 005W** LED POWER SUPPLY MULTI-POWER COMPACT WDL — 1 -> 3 | 1 -> 3 ☐

**Dimtype: WDL = wireless dimmable**

**Cutout dimension (mm): 54**




**21012 0298** LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 — 1 -> 2 | 1 -> 2 ☐

**Dimtype: mains (phase cut-off)**

**Cutout dimension (mm): 48**




**21012 0408** LED POWER SUPPLY 120V - 500mA-DC / 24W DIM8 — - | 2 -> 2 (2) ☐

**Dimtype: mains (phase cut-off)**

**Cutout dimension (mm): 55**

DELTALIGHT

# OVIO 39 ON 93019

40111 9320 W




**21012 0515** LED POWER SUPPLY MULTI POWER DIM5 — 1 -> 1 (1) | 1 -> 1 (1)

**Dimtype: DALI**

**Cutout dimension (mm): 55**




**21012 0595** LED POWER SUPPLY 500mA-DC 10W DIM5 — - | 1 -> 1

**Dimtype: DALI**

**Cutout dimension (mm): 35**

## Light altering devices



**32210 0210** SOFTENING LENS 39



**32210 0220** SANDBLASTED LENS 39



**32210 0230** LINEAR SPREAD LENS 39

**32210 0240** HONEYCOMB 39

Notes: