





SUPERNOVA LINE 95 930 DIM5

20624 9305 B

AVAILABLE IN
BLACK 20624 9305 B
WHITE 20624 9305 W



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted,Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	12.1
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL INCL.DIMMABLE LED POWER SUPPLY
Electrical info	
ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, EPD, RCM
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 147W / CRI>90 (R9: 50) / 3000K / 21588lm
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	21588lm // 147W // 147lm/W
LED TECHNICS (LUMINAIRE)	15871lm // 169W // 94lm/W


Options

SUSPENSION SET 18 DIM1 3m
 CABLE BASE R / S + COVERSET R / S
 CENTRAL ROD SUSPENSION
 SUPERNOVA 95 RECESSED KIT
 WIRELESS CONTROL DIM5

For detailed installation instructions, please consult the manual : [20624_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Current supply



Ø57
41

203 99 55 ANO CABLE BASE R ANO

☐

203 99 55 B CABLE BASE R B

☐

203 99 55 W CABLE BASE R W

☐



57 57
41

203 99 56 ANO CABLE BASE S ANO

☐


203 99 56 B CABLE BASE S B

☐

203 99 56 W CABLE BASE S W

☐

Miscellaneous control equipment



23
50
36


300 90 004 ED5 WIRELESS CONTROL DIM5

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45

☐

Recessed kits



Ø1025
115

274 94 1010 SUPERNOVA 95 RECESSED KIT

Cutout dimension (mm): 1035






☐

DELTALIGHT

SUPERNOVA LINE 95 930 DIM5

20624 9305 B



Coversets

	<u>204 00 62 ANO</u>	COVERSET R 62 ANO	☐
	<u>204 00 62 B</u>	COVERSET R 62 B	☐
	<u>204 00 62 W</u>	COVERSET R 62 W	☐
	<u>204 00 90 ANO</u>	COVERSET R 90 ANO	☐
	<u>204 00 90 B</u>	COVERSET R 90 B	☐
	<u>204 00 90 W</u>	COVERSET R 90 W	☐
	<u>204 00 100 ANO</u>	COVERSET R 100 ANO	☐
	<u>204 00 100 B</u>	COVERSET R 100 B	☐
	<u>204 00 100 W</u>	COVERSET R 100 W	☐
	<u>204 62 62 ANO</u>	COVERSET S 62 ANO	☐
	<u>204 62 62 B</u>	COVERSET S 62 B	☐
	<u>204 62 62 W</u>	COVERSET S 62 W	☐
	<u>204 80 80 ANO</u>	COVERSET S 80 ANO	☐
	<u>204 80 80 B</u>	COVERSET S 80 B	☐




DELTALIGHT

SUPERNOVA LINE 95 930 DIM5

20624 9305 B

	<u>204 80 80 W</u> COVERSET S 80 W	☐
	<u>204 90 90 ANO</u> COVERSET S 90 ANO	☐
	<u>204 90 90 B</u> COVERSET S 90 B	☐
	<u>204 90 90 W</u> COVERSET S 90 W	☐

Suspension parts

	<u>328 18 43 ED1</u> SUSPENSION SET 18 DIM1 3m	☐
	Dimtype: 1-10V	
	<u>328 24 61 B</u> CENTRAL ROD SUSPENSION 65 1m B	☐
	<u>328 24 61 W</u> CENTRAL ROD SUSPENSION 65 1m W	☐
	<u>328 24 91 B</u> CENTRAL ROD SUSPENSION 95 1m B	☐
	<u>328 24 91 W</u> CENTRAL ROD SUSPENSION 95 1m W	☐

Electric connection parts

	<u>15225 0360 B</u> CONNECTION ST B	☐
	Cutout dimension (mm): 43	
	<u>15225 0360 W</u> CONNECTION ST W	☐

DELTALIGHT

SUPERNOVA LINE 95 930 DIM5

20624 9305 B

Notes: