
DELTALIGHT




BOXY L+ 92733 DIM8

REFERENCE 251 67 811 922 ED8 W-W

AVAILABLE IN
ALU GREY-ALU GREY 251 67 811 922 ED8 A-A
BLACK-BLACK 251 67 811 922 ED8 B-B
WHITE-WHITE 251 67 811 922 ED8 W-W





View on website

General info	
LOCATION	indoor-outdoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP53
PROTECTION AGAINST MECHANICAL IMPACT	IK03
WEIGHT (KG)	0.5
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR FL-33° INCL.DIMMABLE POWER SUPPLY 350mA-DC

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	D
CERTIFICATES	CB, EAC, ENEC, LCA, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 60) / 2700K / 753lm
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	33°
LED TECHNICS (LIGHT SOURCE)	753lm // 5,8W // 129lm/W
LED TECHNICS (LUMINAIRE)	601lm // 7W // 90lm/W

For detailed installation instructions, please consult the manual : **251_67_811_XXX_ED8_HAND.pdf**


DELTALIGHT

BOXY L+ 92733 DIM8

251 67 811 922 ED8 W-W

FINISH YOUR SPECIFICATION

Miscellaneous control equipment




300 90 004 ED8 WIRELESS CONTROL DIM8

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 40


☐

Light altering devices




251 70 03 01 B BOXY HONEYCOMB B ☐

251 70 03 01 W BOXY HONEYCOMB W ☐



251 70 03 04 B BOXY SOFTENING LENS B ☐

251 70 03 04 W BOXY SOFTENING LENS W ☐



251 70 03 05 B BOXY GLASS SBL B ☐

251 70 03 05 W BOXY GLASS SBL W ☐

Notes: