





M - DOT.COM WALLWASH 02 927 HO MDL

424 642 02 92 MDL B

AVAILABLE IN
BLACK 424 642 02 92 MDL B



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	non adjustable
INFORMATION	EXCL.LED POWER SUPPLY 48V-DC
Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	F
CERTIFICATES	CB, EAC, ENEC, EPD
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 9,6W / CRI>90 (R9: 63) / 2700K / 998lm
TM-30 VALUES	Rf: 89 / Rg: 96
SDCM	SDCM3
LM80	L70 > 60000
LED TECHNICS (LIGHT SOURCE)	998lm // 9,6W // 104lm/W
LED TECHNICS (LUMINAIRE)	543lm // 11W // 49lm/W

Remarks

[Take a look at our MAGNETIC PROFILES movie](#)

Requirements

LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR

For detailed installation instructions, please consult the manual : [424_642_02_9X_MD_L HAND.pdf](#)

FINISH YOUR SPECIFICATION

Current supply

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



21032 0030 SMART 48 MODULATOR PLUG-IN WD

16

Dimtype: WDL = wireless dimmable

SMART 48

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



300 90 011 SMART 48 MODULATOR DIM9

16

Dimtype: 1-10V or DALI or push button



300 90 012 SMART 48 MODULATOR WD

16

Dimtype: WDL = wireless dimmable


LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



300 89 48 90 LED POWER SUPPLY 48V-DC / 90W

8

Dimtype: non-dimmable

Cutout dimension (mm): 75



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN





8

Dimtype: non-dimmable





DELTALIGHT

M - DOT.COM WALLWASH 02 927 HO MDL

424 642 02 92 MDL B

	300 89 48 150 LED POWER SUPPLY 48V-DC / 150W	13	☐
Dimtype: non-dimmable			
	300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN	20	☐
Dimtype: non-dimmable			
	21012 0230 LED POWER SUPPLY 48V-DC / 100W	8	☐
Dimtype: non-dimmable			
Cutout dimension (mm): 40			
	21012 0240 LED POWER SUPPLY 48V-DC / 200W	17	☐
Dimtype: non-dimmable			
Cutout dimension (mm): 40			




COMPATIBLE COMPOSABLES

SHIFTLINE M26 profile		Available Colours
	<u>420 26 10 00</u> SLM26 - PROFILE 1m	
	<u>420 26 20 00</u> SLM26 - PROFILE 2m	
	<u>420 26 30 00</u> SLM26 - PROFILE 3m	
SHIFTLINE M26H profile		Available Colours
	<u>23359 0000</u> SLM26H - PROFILE	 

DELTALIGHT

M - DOT.COM WALLWASH 02 927 HO MDL

424 642 02 92 MDL B

	23359 0010 SLM26H - PROFILE 1m	
	23359 0020 SLM26H - PROFILE 2m	
	23359 0030 SLM26H - PROFILE 3m	




SPLITLINE M20 ST profile

Available Colours

	23397 0000 SPM20 ST - PROFILE	
	23397 0020 SPM20 ST - PROFILE 2m	
	23397 0030 SPM20 ST - PROFILE 3m	

SPLITLINE M20 profile

Available Colours

	420 20 10 00 SPM20 - PROFILE 1m	
	420 20 20 00 SPM20 - PROFILE 2m	
	420 20 30 00 SPM20 - PROFILE 3m	

M - DOT.COM WALLWASH 02 927 HO MDL

424 642 02 92 MDL B



23301 0000 SPM20 - PROFILE B



Notes: