



INFORM SQ P585-9 DOWN 93067

25574 9320 B-FG



AVAILABLE IN

BLACK-BLACK 25574 9320 B-B

BLACK-FLEMISH GOLD 25574 9320 B-FG

WHITE-BLACK 25574 9320 W-B

WHITE-WHITE 25574 9320 W-W



 [View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	4.6
ADJUSTABILITY	non adjustable
INFORMATION	108 x REFLECTOR FL-67° EXCL.LED POWER SUPPLY 900/1350mA-DC INCL.4 x CABLE SUSPENSION SINGLE AUTO. 1,6m INCL.1 x CABLE 2 x 0.75mm ²

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	3 x (LED cluster 10,5-16,7W / CRI>90 (R9: 50) / 3000K / 1602-2315lm)
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
BEAMANGLE	67°
LED TECHNICS (LIGHT SOURCE)	6945lm // 50,1W // 138lm/W
LED TECHNICS (LUMINAIRE)	6063lm // 57,6W // 105lm/W

Requirements

INFORM POWER SUPPLY 60W
INFORM SQ POWERBOX L 75W

Options

CABLE BASE R / S
COVERSET R 62-90-100 / S 62-80-90
CONNECTION ST / CONNECTION TRIMLESS
SUSPENSION ST / SUSPENSION TRIMLESS

DELTALIGHT


INFORM SQ P585-9 DOWN 93067

25574 9320 B-FG

For detailed installation instructions, please consult the manual : [25574_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Current supply



203 99 55 ANO CABLE BASE R ANO

203 99 55 B CABLE BASE R B

203 99 55 W CABLE BASE R W



203 99 56 ANO CABLE BASE S ANO

203 99 56 B CABLE BASE S B

203 99 56 W CABLE BASE S W


LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



25510 0405 INFORM POWER SUPPLY 60W DIM5

1

Dimtype: DALI



25510 0450 INFORM POWER SUPPLY 60W

1

Dimtype: non-dimmable

DELTALIGHT

INFORM SQ P585-9 DOWN 93067

25574 9320 B-FG

Power box

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



25510 0500 B INFORM SQ POWERBOX L 75W B

1

Dimtype: non-dimmable

25510 0500 W INFORM SQ POWERBOX L 75W W

1



25510 0515 B INFORM SQ POWERBOX L 75W DIM5 B


1

Dimtype: DALI

25510 0515 W INFORM SQ POWERBOX L 75W DIM5 W

1

Coversets



204 00 62 ANO COVERSET R 62 ANO

204 00 62 B COVERSET R 62 B


204 00 62 W COVERSET R 62 W



204 00 90 ANO COVERSET R 90 ANO

204 00 90 B COVERSET R 90 B

204 00 90 W COVERSET R 90 W



204 00 100 ANO COVERSET R 100 ANO

DELTALIGHT

INFORM SQ P585-9 DOWN 93067

25574 9320 B-FG

204 00 100 B COVERSET R 100 B

204 00 100 W COVERSET R 100 W



204 62 62 ANO COVERSET S 62 ANO

204 62 62 B COVERSET S 62 B


204 62 62 W COVERSET S 62 W



204 80 80 ANO COVERSET S 80 ANO

204 80 80 B COVERSET S 80 B

204 80 80 W COVERSET S 80 W




204 90 90 ANO COVERSET S 90 ANO

204 90 90 B COVERSET S 90 B


204 90 90 W COVERSET S 90 W

Suspension parts



328 10 01 SUSPENSION TRIMLESS O.F.A.

Cutout dimension (mm): 62 (CONCRETE: 102)



15225 0340 B SUSPENSION ST B

Cutout dimension (mm): 27

DELTALIGHT

INFORM SQ P585-9 DOWN 93067

25574 9320 B-FG

15225 0340 W SUSPENSION ST W

Electric connection parts



328 10 03 CONNECTION TRIMLESS O.F.A.

Cutout dimension (mm): 62 (CONCRETE: 102)



15225 0360 B CONNECTION ST B

Cutout dimension (mm): 43

15225 0360 W CONNECTION ST W

Notes: