



INFORM 40 SQ FT T DOWN-UP 930



100090 9300 W-B

AVAILABLE IN

ALU GREY-BLACK 100090 9300 A-B

BLACK-BLACK 100090 9300 B-B

WHITE-BLACK 100090 9300 W-B



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Floor Stand alone
INGRESS PROTECTION	IP20
WEIGHT (KG)	10
ADJUSTABILITY	non adjustable
INFORMATION	INCL.1 x CABLE 3 x 0.75mm ² 2m + CEE 7/7 plug 2 control buttons : 1: UP ON/OFF + DIM 2: DOWN ON/OFF + DIM UGR ≤ 13

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	control button on luminaire
ENERGY CLASS	D
CERTIFICATES	EPD, LCA

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: LED cluster 16,4W / CRI>90 / 3000K / 2614lm UP: LED cluster 45,5W / CRI>90 / 3000K / 7891lm
TM-30 VALUES	Rf: 93 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	DOWN: 2614lm // 16,4W // 160lm/W UP: 7891lm // 45,5W // 174lm/W
LED TECHNICS (LUMINAIRE)	DOWN: 1540lm // 18,9W // 82lm/W UP: 7307lm // 52,3W // 140lm/W

For detailed installation instructions, please consult the manual : [100090_XXX0_HAND.pdf](#)

DELTALIGHT

INFORM 40 SQ FT T DOWN-UP 930

100090 9300 W-B

Notes: