



M26L - SPY 52 WALLWASH SOFT 930 DIM5

19893 9005 FBR

AVAILABLE IN

NOIR 19893 9005 B

FLEMISH BRONZE 19893 9005 FBR

FLEMISH GOLD 19893 9005 FG

COULEUR OR 19893 9005 GC

BLANC 19893 9005 W



[View on website](#)



General info

LOCATION	interieur
INSTALLATION	Systèmes basse tension Monté sur systèmes basse tension
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° à 90° inclinable, 360° rotatif
INFORMATION	WALLWASH LENS EXCLLED POWER SUPPLY 48V-DC

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	F
CERTIFICATION	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 10,2W / CRI>90 (R9: 50) / 3000K-1800K / 1038lm
SDMC	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1038lm // 10,2W // 109lm/W
LED TECHNICS (LUMINAIRE)	490lm // 11,7W // 42lm/W

Remarks

Take a look at our [MAGNETIC PROFILES movie](#)

Requirements





LED POWER SUPPLY 48V-DC

For detailed installation instructions, please consult the manual : [19893_XXX5_HAND.pdf](#)




M26L - SPY 52 WALLWASH SOFT 930 DIM5

19893 9005 FBR

FINISH YOUR SPECIFICATION

les alimentations led			# of Fixtures
 web2print_power_supply_info_box			Min current Max current
 300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN	8		☐
Dimtype: non dimmable			
 300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN	20		☐
Dimtype: non dimmable			
 21012 0230 LED POWER SUPPLY 48V-DC / 100W	8		☐
Dimtype: non dimmable			
Cutout dimension (mm): 40			
 21012 0240 LED POWER SUPPLY 48V-DC / 200W	17		☐
Dimtype: non dimmable			
Cutout dimension (mm): 40			

COMPATIBLE COMPOSABLES

SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)	Available Colours
 23358 0000 SLM26L - PROFILE	 
 23358 0010 SLM26L - PROFILE 1m	 
 23358 0020 SLM26L - PROFILE 2m	          

DELTALIGHT

M26L - SPY 52 WALLWASH SOFT 930 DIM5

19893 9005 FBR



23358 0030 SLM26L - PROFILE 3m



Notes: