
DELTALIGHT





# SUPERLOOP HC 90 SBL 930

**REFERENCE** 321 109 93 B

AVAILABLE IN
**BLACK** 321 109 93 B
**FLEMISH BRONZE** 321 109 93 FBR
**FLEMISH GOLD** 321 109 93 FG
**WHITE** 321 109 93 W




View on website

| General info | |
|---|---|
| **LOCATION** | indoor |
| **INSTALLATION** | Ceiling Suspended |
| **INGRESS PROTECTION** | IP20 |
| **WEIGHT (KG)** | 3 |
| **ADJUSTABILITY** | non adjustable |
| **INFORMATION** | INCL.PC SBL<br>EXCL.LED POWER SUPPLY 700-900mA-DC<br>INCL.3 x CABLE SUSPENSION SINGLE AUTO. 3.0m<br>INCL.1 x CABLE 2 x 0.75mm² |

| Electrical info | |
|---|---|
| **CLASS** | III |
| **DIM TYPE** | depending on power supply |
| **ENERGY CLASS** | E |
| **CERTIFICATES** | CB, EAC, ENEC, EPD |

| Lightsource info | |
|---|---|
| **LIGHTSOURCE NAME** | LED |
| **LIGHTSOURCE** | LED cluster 28,2-39W / CRI>90 (R9: 59) / 3000K / 3888-5160lm |
| **SDCM** | SDCM3 |
| **LM80** | L70 > 30000 |
| **LED TECHNICS (LIGHT SOURCE)** | 5160lm // 39W // 132lm/W |
| **LED TECHNICS (LUMINAIRE)** | 3101lm // 44,8W // 69lm/W |

**Requirements**

LED POWER SUPPLY 700 / 900mA-DC DIM
SUPERLOOP POWERBOX L/H 700mA
SUPERLOOP POWERBOX H 900mA

**Options**

CABLE BASE R / S
COVERSET R 62-90-100 / S 62-80-90
CONNECTION ST / CONNECTION TRIMLESS
SUSPENSION ST / SUSPENSION TRIMLESS

For detailed installation instructions, please consult the manual : **321_X09_93_HAND.pdf**


DELTALIGHT

# SUPERLOOP HC 90 SBL 930

321 109 93 B

## FINISH YOUR SPECIFICATION

### Current supply




**203 99 55 ANO** CABLE BASE R ANO

**203 99 55 B** CABLE BASE R B

**203 99 55 W** CABLE BASE R W




**203 99 56 ANO** CABLE BASE S ANO

**203 99 56 B** CABLE BASE S B


**203 99 56 W** CABLE BASE S W

### Power box

### # of Fixtures

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


**Min current | Max current**




**321 55 207 ED1 B** SUPERLOOP POWERBOX L 700mA DIM1 B — 1

**Dimtype: 1-10V**

**321 55 207 ED1 W** SUPERLOOP POWERBOX L 700mA DIM1 W — 1




**321 55 309 ED5 B** SUPERLOOP POWERBOX H 900mA DIM5 B — 1


**Dimtype: DALI**

**321 55 309 ED5 W** SUPERLOOP POWERBOX H 900mA DIM5 W — 1

DELTALIGHT

# SUPERLOOP HC 90 SBL 930

321 109 93 B




**20548 0015 B** SUPERLOOP POWERBOX H9 900mA DIM5 B — 1

**Dimtype: DALI**


**20548 0015 W** SUPERLOOP POWERBOX H9 900mA DIM5 W — 1

## LED power supplies

## # of Fixtures

# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


**Min current | Max current**




**300 90 128** LED POWER SUPPLY 700mA-DC / 36W DIM1 — 1

**Dimtype: 1-10V**


**Cutout dimension (mm): 54**




**300 90 129** LED POWER SUPPLY 900mA-DC / 60W DIM5 — 1

**Dimtype: DALI**

**Cutout dimension (mm): 84**





**300 90 131** LED POWER SUPPLY 700mA-DC / 38W DIM5 — 1

**Dimtype: DALI**

**Cutout dimension (mm): 54**


## Coversets




**204 00 62 ANO** COVERSET R 62 ANO

**204 00 62 B** COVERSET R 62 B

**204 00 62 W** COVERSET R 62 W








**204 00 90 ANO** COVERSET R 90 ANO

DELTALIGHT

# SUPERLOOP HC 90 SBL 930

321 109 93 B


| | | | |
|---|---|---|---|
| | **204 00 90 B** | COVERSET R 90 B | ☐ |
| | **204 00 90 W** | COVERSET R 90 W | ☐ |
|  | **204 00 100 ANO** | COVERSET R 100 ANO | ☐ |
| | **204 00 100 B** | COVERSET R 100 B | ☐ |
| | **204 00 100 W** | COVERSET R 100 W | ☐ |
|  | **204 62 62 ANO** | COVERSET S 62 ANO | ☐ |
| | **204 62 62 B** | COVERSET S 62 B | ☐ |
| | **204 62 62 W** | COVERSET S 62 W | ☐ |
|  | **204 80 80 ANO** | COVERSET S 80 ANO | ☐ |
| | **204 80 80 B** | COVERSET S 80 B | ☐ |
| | **204 80 80 W** | COVERSET S 80 W | ☐ |
|  | **204 90 90 ANO** | COVERSET S 90 ANO | ☐ |
| | **204 90 90 B** | COVERSET S 90 B | ☐ |
| | **204 90 90 W** | COVERSET S 90 W | ☐ |

DELTALIGHT

# SUPERLOOP HC 90 SBL 930


321 109 93 B

## Suspension parts




**328 10 01** SUSPENSION TRIMLESS O.F.A.

**Cutout dimension (mm): 62 (CONCRETE: 102)**





**15225 0340 B** SUSPENSION ST B

**Cutout dimension (mm): 27**

**15225 0340 W** SUSPENSION ST W

## Electric connection parts




**328 10 03** CONNECTION TRIMLESS O.F.A.

**Cutout dimension (mm): 62 (CONCRETE: 102)**




**15225 0360 B** CONNECTION ST B

**Cutout dimension (mm): 43**

**15225 0360 W** CONNECTION ST W

Notes: