

FRAX SB 92726 HONEYCOMB



26000 9270 FBRX

AVAILABLE IN

FLEMISH BRONZE OUTDOOR 26000 9270 FBRX

ANTHRACITE 26000 9270 N

PINE GREEN 26000 9270 PGR



 [View on website](#)



General info

LOCATION	outdoor
INSTALLATION	Floor Surface mounted, Wall Surface mounted
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK06
WEIGHT (KG)	1.3
ADJUSTABILITY	0° to 120° swiveling, 360° rotatable
INFORMATION	4 x LENS SP-14° INCL.LED POWER SUPPLY 700mA-DC INCL.BEAM LENS 26° INCL.HONEYCOMB INCL.1 x CABLE H05 RN-F 3 x 1mm ² 2m

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 8W / CRI>90 (R9: 50) / 2700K / 878lm
TM-30 VALUES	Rf: 91 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 150000
BEAMANGLE	26°
LED TECHNICS (LIGHT SOURCE)	878lm // 8W // 110lm/W
LED TECHNICS (LUMINAIRE)	492lm // 9,2W // 53lm/W

Requirements

FRAX BRACKET
FRAX PIN
FRAX STRAP

Options

FRAX ANTI VANDAL SCREWS

Accessories

FRAX S KAP

DELTALIGHT

FRAX SB 92726 HONEYCOMB

26000 9270 FBRX

For detailed installation instructions, please consult the manual : [26000_XX70_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Pins and plates for bollards



26070 0040 FBRX FRAX PIN FBRX

26070 0040 N FRAX PIN N

26070 0040 PGR FRAX PIN PGR

Fixation components



26070 0060 FBRX FRAX BRACKET FBRX

26070 0060 N FRAX BRACKET N

26070 0060 PGR FRAX BRACKET PGR

Light altering devices




26070 0010 N FRAX S KAP N

DELTALIGHT

FRAX SB 92726 HONEYCOMB

26000 9270 FBRX

Other



26070 0030 FRAX ANTI VANDAL SCREWS 5 PCS



26070 0050 N FRAX STRAP N



Notes: