



## LOGIC LINEAR ON 880 92725 DIM5

30835 9225 N

AVAILABLE IN



**ALU GREY** 30835 9225 A

**BLACK** 30835 9225 B

**FLEMISH BRONZE OUTDOOR** 30835 9225 FBRX

**ANTHRACITE** 30835 9225 N

**WHITE** 30835 9225 W



[View on website](#)



| General info                         |                                                                      |
|--------------------------------------|----------------------------------------------------------------------|
| LOCATION                             | outdoor                                                              |
| INSTALLATION                         | Floor Surface mounted, Wall Surface mounted                          |
| INGRESS PROTECTION                   | IP67                                                                 |
| PROTECTION AGAINST MECHANICAL IMPACT | IK07                                                                 |
| WEIGHT (KG)                          | 2                                                                    |
| INFORMATION                          | 16 x LENS FL-25°<br>EXCL.LED POWER SUPPLY 48V-DC<br>DALI DT8 dimming |
| Electrical info                      |                                                                      |
| ELECTRICAL                           | 48V-DC                                                               |
| CLASS                                | III                                                                  |
| DIM TYPE                             | DALI                                                                 |
| ENERGY CLASS                         | F                                                                    |
| CERTIFICATES                         | CB, ENEC                                                             |
| Lightsource info                     |                                                                      |
| LIGHTSOURCE NAME                     | LED                                                                  |
| LIGHTSOURCE                          | LED cluster 28,8W / CRI>90 (R9: 55) / 2700K / 3288lm                 |
| TM-30 VALUES                         | Rf: 91 / Rg: 100                                                     |
| SDCM                                 | SDCM3                                                                |
| RISKGROUP                            | RG2                                                                  |
| LM80                                 | L80 > 150000                                                         |
| BEAMANGLE                            | 25°                                                                  |
| LED TECHNICS (LIGHT SOURCE)          | 3288lm // 28,8W // 111lm/W                                           |
| LED TECHNICS (LUMINAIRE)             | 2722lm // 33,1W // 82lm/W                                            |

### Requirements

WALL BRACKET SET  
FLOOR BRACKET SET  
IP68 CABLE + CONNECTOR 5P  
LED POWER SUPPLY 48V-DC

### Options

THROUGH WIRING SET IP68

For detailed installation instructions, please consult the manual : [30835\\_XXX5\\_HAND.pdf](#)


### FINISH YOUR SPECIFICATION

#### LED power supplies

#### # of Fixtures

**i** # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



**21032 0390** LED POWER SUPPLY 48V-DC / 90W

**Dimtype: non-dimmable**

**Cutout dimension (mm): 75**

2

#### Fixation components



**30810 0040**

LOGIC LINEAR 880 BOX EXTEND

**30810 0040 INOX** WALL BRACKET SET 60 INOX

**30810 0040 N**

WALL BRACKET SET 60 N




**30810 0050 INOX**

WALL BRACKET SET 100 INOX

**30810 0050 N**

WALL BRACKET SET 100 N



**30810 0060 INOX**

WALL BRACKET SET 200 INOX

**30810 0060 N**

WALL BRACKET SET 200 N

# DELTALIGHT

## LOGIC LINEAR ON 880 92725 DIM5

30835 9225 N



**30810 0070 INOX** FLOOR BRACKET SET INOX

☐

### Electric connection parts



**30810 0080** IP68 CABLE + CONNECTOR 5P - 0,5m

☐

**30810 0090** IP68 CABLE + CONNECTOR 5P - 2m

☐

**30810 0110** THROUGH WIRING SET IP68 880

☐

Notes: