
DELTALIGHT




LASS-OH! L150-3 92734

REFERENCE 24816 9220 B

AVAILABLE IN
BLACK 24816 9220 B
GOLD COLOURED 24816 9220 GC





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.6
ADJUSTABILITY	non adjustable
INFORMATION	INCL.3 x DOT.COM S6 modules per module: 6 x REFLECTOR FL-34° EXCL.LED POWER SUPPLY 1050mA-DC INCL.2 x CABLE SUSPENSION SINGLE AUTO. 1,6m INCL.1 x CABLE 2 x 0.75mm²

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, EAC, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	3 x (LED cluster 6,1W / CRI>90 (R9: 50) / 2700K / 665lm)
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
LM80	L80 > 60000
BEAMANGLE	34°
LED TECHNICS (LIGHT SOURCE)	1995lm // 18,3W // 109lm/W
LED TECHNICS (LUMINAIRE)	1577lm // 21W // 75lm/W

Requirements

LASS-OH! POWERBOX
LED POWER SUPPLY 1050mA-DC DIM

Options

CABLE BASE R / S
COVERSET R 62-90-100 / S 62-80-90
CONNECTION ST / CONNECTION TRIMLESS
SUSPENSION ST / SUSPENSION TRIMLESS

Accessories

JIHA S / R

DELTALIGHT


LASS-OH! L150-3 92734

24816 9220 B

For detailed installation instructions, please consult the manual : **24816_XXXX_HAND.pdf**

FINISH YOUR SPECIFICATION


Current supply



203 99 55 ANO CABLE BASE R ANO

203 99 55 B CABLE BASE R B

203 99 55 W CABLE BASE R W



203 99 56 ANO CABLE BASE S ANO

203 99 56 B CABLE BASE S B


203 99 56 W CABLE BASE S W

LED power supplies

of Fixtures

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



21012 0010 LED POWER SUPPLY MULTI POWER — 1

Dimtype: non-dimmable

Cutout dimension (mm): 50



21012 0021 LED POWER SUPPLY MULTI POWER DIM1 — 1


Dimtype: 1-10V

Cutout dimension (mm): 54

DELTALIGHT

LASS-OH! L150-3 92734

24816 9220 B



21012 0035 LED POWER SUPPLY MULTI POWER DIM5 — 1

Dimtype: DALI


Cutout dimension (mm): 54

Power box

of Fixtures


Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.




24814 0010 B LASS-OH! POWERBOX B — 1

Dimtype: non-dimmable



24814 0011 B LASS-OH! POWERBOX DIM1 B — 1


Dimtype: 1-10V



24814 0015 B LASS-OH! POWERBOX DIM5 B — 1

Dimtype: DALI


Coversets



204 00 62 ANO COVERSET R 62 ANO

204 00 62 B COVERSET R 62 B

204 00 62 W COVERSET R 62 W







204 00 90 ANO COVERSET R 90 ANO

204 00 90 B COVERSET R 90 B

DELTALIGHT

LASS-OH! L150-3 92734

24816 9220 B


	204 00 90 W COVERSET R 90 W	☐
	**204 00 100 ANO** COVERSET R 100 ANO	☐
	204 00 100 B COVERSET R 100 B	☐
	204 00 100 W COVERSET R 100 W	☐
	**204 62 62 ANO** COVERSET S 62 ANO	☐
	204 62 62 B COVERSET S 62 B	☐
	204 62 62 W COVERSET S 62 W	☐
	**204 80 80 ANO** COVERSET S 80 ANO	☐
	204 80 80 B COVERSET S 80 B	☐
	204 80 80 W COVERSET S 80 W	☐
	**204 90 90 ANO** COVERSET S 90 ANO	☐
	204 90 90 B COVERSET S 90 B	☐
	204 90 90 W COVERSET S 90 W	☐

DELTALIGHT

LASS-OH! L150-3 92734


24816 9220 B

Suspension parts



328 10 01 SUSPENSION TRIMLESS O.F.A.

Cutout dimension (mm): 62 (CONCRETE: 102)




15225 0340 B SUSPENSION ST B

Cutout dimension (mm): 27

15225 0340 W SUSPENSION ST W

Electric connection parts



328 10 03 CONNECTION TRIMLESS O.F.A.

Cutout dimension (mm): 62 (CONCRETE: 102)




15225 0360 B CONNECTION ST B


Cutout dimension (mm): 43

15225 0360 W CONNECTION ST W

Light altering devices



24814 0020 B JIHA! S B



24814 0030 B JIHA! R B

LASS-OH! L150-3 92734

24816 9220 B

Notes: