DELTALIGHT

DOT.COM L4 ST 92746

REFERENCE 424 213 04 923 W-C

AVAILABLE IN
BLACK-BLACK 424 213 04 923 B-B
BLACK-CHROMED 424 213 04 923 B-C
BLACK-FLEMISH GOLD 424 213 04 923 B-FG
WHITE-BLACK 424 213 04 923 W-B
WHITE-CHROMED 424 213 04 923 W-C
WHITE-FLEMISH GOLD 424 213 04 923 W-FG





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	rectangle - 158 x 40
RECESSED DEPTH (MM)	62
THICKNESS OF MOUNTING SURFACE (MM)	max.30
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.4
ADJUSTABILITY	non adjustable
INFORMATION	4 x REFLECTOR WFL-46° EXCL.LED POWER SUPPLY 500-1050mA-DC

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	F
CERTIFICATES	CB, EAC, ENEC, LCA

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 5,7-12,6W / CRI>90 (R9: 50) / 2700K / 631-1194lm
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 60000
BEAMANGLE	46°
LED TECHNICS (LIGHT SOURCE)	1194lm // 12,6W // 95lm/W
LED TECHNICS (LUMINAIRE)	686lm // 14,5W // 47lm/W

Requirements

LED POWER SUPPLY 500 / 1050mA-DC DIM

For detailed installation instructions, please consult the manual : **424_213_04_XXX_HAND.pdf**

DELTALIGHT

DOT.COM L4 ST 92746

424 213 04 923 W-C

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
System ceiling	-
Plasterboard	-
Stucanet	-
Wood	-
Stretched ceiling	-

FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



300 48 500 ED1 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1 — 3 ☐

Dimtype: 1-10V

Cutout dimension (mm): 30



300 48 500 ED5 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5 — 3 ☐

Dimtype: DALI

Cutout dimension (mm): 45



300 48 500 MDL LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL — 3 ☐

Dimtype: non-dimmable

Cutout dimension (mm): 30



300 48 500 WDL LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL — 3 ☐

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45

DOT.COM L4 ST 92746

424 213 04 923 W-C



300 48 700 ED1 LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM1 — 3

Dimtype: 1-10V

Cutout dimension (mm): 30



300 48 700 ED5 LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM5 — 3

Dimtype: DALI

Cutout dimension (mm): 45



300 48 700 MDL LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W MDL — 3

Dimtype: non-dimmable

Cutout dimension (mm): 30



300 48 700 WDL LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W WDL — 3

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45



300 90 61 LED POWER SUPPLY MULTI-POWER DIM6 — 4 | 3

Dimtype: mains (phase cut-off) or push button

Cutout dimension (mm): 56



300 90 63 LED POWER SUPPLY MULTI-POWER DIM9 — 6(6) | 6(4) | 4(3)

Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 82



300 90 64 LED POWER SUPPLY MULTI-POWER DIM7 — 4(2) | 3(1)

Dimtype: 1-10V or push button

Cutout dimension (mm): 72



300 90 67 LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9 — 3 | 3

Dimtype: 1-10V or DALI or push button



300 90 68 LED POWER SUPPLY MULTI-POWER DIM5 — 4(2) | 3(1) | -

Dimtype: DALI

Cutout dimension (mm): 72



300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9 — 9(7) | 7(4) | -

Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 84

DOT.COM L4 ST 92746

424 213 04 923 W-C



300 90 124 LED POWER SUPPLY MULTI-POWER DIM7 3(2) | 2(1) | -

Dimtype: 1-10V or push button

Cutout dimension (mm): 55

300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5 3(2) | 2(1) | -

Dimtype: DALI

Cutout dimension (mm): 55



300 90 135 LED POWER SUPPLY MULTI-POWER HV 3->7 | 3->7 | 3->5

Dimtype: non-dimmable

Cutout dimension (mm): 90



300 90 136 LED POWER SUPPLY MULTI-POWER HC DIM9 3(3)

Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 90



300 90 148 LED POWER SUPPLY 1050mA-DC / 22W 1(0)

Dimtype: non-dimmable

Cutout dimension (mm): 48



21012 0010 LED POWER SUPPLY MULTI POWER 3 | 3 | 3

Dimtype: non-dimmable

Cutout dimension (mm): 50



21012 0021 LED POWER SUPPLY MULTI POWER DIM1 4 | 4 | 2

Dimtype: 1-10V

Cutout dimension (mm): 54



21012 0035 LED POWER SUPPLY MULTI POWER DIM5 4 | 4 | 3

Dimtype: DALI

Cutout dimension (mm): 54



21012 004W LED POWER SUPPLY MULTI-POWER WDL 6(6) | 6(4) | 4(3)

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 84



21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL 4 | 4 | 3

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 54

DELTALIGHT

DOT.COM L4 ST 92746

424 213 04 923 W-C



21012 0278 LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8 2->2 | 2->2 | -

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 55



21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8 3->4 | 3->4 | -

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 55



21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 3 | 2 | -

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 48



21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5 3

Dimtype: DALI

Cutout dimension (mm): 30



21032 0315 LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM5 3

Dimtype: DALI

Cutout dimension (mm): 30

Notes: