





OCTAV 39 ON 2 92740 DIM8

29019 9238 B-B

AVAILABLE IN

BLACK-BLACK 29019 9238 B-B

WHITE-WHITE 29019 9238 W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.8
ADJUSTABILITY	0° to 85° swiveling, 355° rotatable
INFORMATION	REFLECTOR WFL-40° INCL.DIMMABLE LED POWER SUPPLY 350/500mA-DC Current selection via jumper on power supply

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED array 8,6W / CRI>90 (R9: 60) / 2700K / 1041lm)
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	40°
LED TECHNICS (LIGHT SOURCE)	2082lm // 17,2W // 121lm/W
LED TECHNICS (LUMINAIRE)	1410lm // 19,8W // 71lm/W

Requirements

SPY 39 L TUBE

For detailed installation instructions, please consult the manual : [29019_XXX8_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Finish your product

	<u>24144 0020 B</u>	SPY 39 L TUBE B	☐
	<u>24144 0020 FBR</u>	SPY 39 L TUBE FBR	☐
	<u>24144 0020 FG</u>	SPY 39 L TUBE FG	☐
	<u>24144 0020 GC</u>	SPY 39 L TUBE GC	☐
	<u>24144 0020 W</u>	SPY 39 L TUBE W	☐

Notes: