
DELTALIGHT




# OONO W M 930 DIM8

**REFERENCE** 29612 9308 N

AVAILABLE IN
**ALU GREY** 29612 9308 A
**BLACK** 29612 9308 B
**FLEMISH BRONZE OUTDOOR** 29612 9308 FBRX
**GOLD MARBLED** 29612 9308 GM
**ANTHRACITE** 29612 9308 N
**WHITE** 29612 9308 W



View on website

| General info | |
|---|---|
| **LOCATION** | indoor-outdoor |
| **INSTALLATION** | Wall Surface mounted |
| **INGRESS PROTECTION** | IP54 |
| **PROTECTION AGAINST MECHANICAL IMPACT** | IK04 |
| **WEIGHT (KG)** | 2.6 |
| **ADJUSTABILITY** | non adjustable |
| **INFORMATION** | INCL.DIMMABLE LED POWER SUPPLY 700mA-DC<br>GM (Gold Marbled) version only for interior use |

| Electrical info | |
|---|---|
| **ELECTRICAL** | 220-240V / 50-60Hz |
| **CLASS** | I |
| **POWER SUPPLY** | YES |
| **DIM TYPE** | mains (phase cut-off) |
| **ENERGY CLASS** | E |

| Lightsource info | |
|---|---|
| **LIGHTSOURCE NAME** | LED |
| **LIGHTSOURCE** | LED array 12,4W / CRI>90 (R9: 52) / 3000K / 1467lm |
| **TM-30 VALUES** | Rf: 90 / Rg: 99 |
| **SDCM** | SDCM1 |
| **RISKGROUP** | RG1 |
| **LM80** | L90B10 > 50000 |
| **LED TECHNICS (LIGHT SOURCE)** | 1467lm // 12,4W // 118lm/W |
| **LED TECHNICS (LUMINAIRE)** | 773lm // 14,3W // 54lm/W |

For detailed installation instructions, please consult the manual : **29612_XXX8_HAND.pdf**

Notes:

## OONO W M 930 DIM8

29612 9308 N